

Hinged cover for adjustable floor box or service cover in concrete or raised floor for 4 elements graphite Simon 500 Cima

REF. RSF002/14



BASIC INFORMATION

DESCRIPTION

Hinged cover for adjustable floor box or service cover in concrete or raised floor box with 4 elements included in the Simon 500 Cima series. With graphite finish, this piece has dimensions of 145 x 161 x 15 mm and is manufactured in plastic, although it contains certain, although metal elements with halogen-free thermoplastic, this material is halogen-free and is self-extinguishing, features that prevent the extension of the flame in case of fire. The adjustable floor boxes are delivered with a hinged cover. You only need to order it as a replacement if it is broken or is lost. Maintenance is easy, all you need to do is to use a soft, dry cloth and avoid abrasive cleaners. The Simon 500 Cima series is a collection that focuses on the workplace solutions in all kinds of spaces. Proof of this is its wide range of products and kits.

FINISH

Graphite

PACKAGING CONTENTS

Hinged cover

MATERIAL

Plastic

ETIM CLASS

EC001903

REMARKS

The adjustable floor boxes include the hinged cover. Only necessary to order it as a replacement part in the event of breakage or loss.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

PROTECTION AGAINST DIRECT ACCESS OF CONTACTS

No

PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS

Yes, thanks to the inclusion of protective foam

AVAILABLE IN

2, 4, 6, 8 and 12 elements

DIELECTRIC STRENGTH

No holes or contours, with 2000V at 50 Hz for 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)

+90 °C

HEAT RESISTANCE (°C)

+125°C (according rule IEC 60695-10-2)

INSULATION RESISTANCE (V-MΩ)

>5 MOhms at 500V

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60 °C

NUMBER OF MODULES

4 modules

RAL

7021

VERSION

4 elements

INSTALLATION AND MAINTENANCE

TYPE OF FASTENING

Via coupling pin supplied on the cover

INSTALLATION DIRECTION

Horizontal and vertical, in accordance with the installation of the floor box or service cover

INSTALLATION TYPE

In raised or concrete floor with adjustable floor boxes or service covers

REGULATIONS

REGULATIONS

UNE-EN 60.670-23

LOGISTICS INFORMATION

UNITARY EAN CODE

8426436056206

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.494

PRODUCT NET WEIGHT

0.494

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8426436056206

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

20

PACKAGING WIDTH

350

PACKAGING LENGTH

250

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

1.75

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

0.494

PACKAGING WEIGHT UNIT

KGM