Bipolar thermal-magnetic 10A with double 1 element trim plate and 32 mm height graphite Simon Cima

REF. **SMS/14**



BASIC INFORMATION

FINISH

Graphite

COMPATIBILITY

With Cima Classic surface-mounted wall boxes, Cima Classic flush-mounted wall boxes with a 60mm housing, Cima towers, and Cima columns and mini columns.

ETIM CLASS

EC000042

TECHNICAL INFORMATION

BREAKING CAPACITY (A)
6000 A

CURRENT (A)
10 A

IP RATING
IP20

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

POWER SUPPLY (V~)
400 V~

RAL
7021

TRIP CURVE
C Curve

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)
10

INSTALLATION DIRECTION
Horizontal, Vertical

REMOVAL OF THE MCB
Only with tool

TYPE OF TERMINAL CONNECTION - FUNCTION 1
Screw

LOGISTICS INFORMATION

UNITARY EAN CODE
8426436032842

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
3878784

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
0.321

PRODUCT NET WEIGHT
0.321

UNITARY PACKAGING WEIGHT UNIT
KGM

UNITS CONTAINED PACKAGING
5

PACKAGING HEIGHT
118

PACKAGING WIDTH
121

PACKAGING LENGTH
264

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
3769392

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.16

PACKAGING NET WEIGHT
1.605

PACKAGING WEIGHT UNIT
KGM