19" ELECTROBLOCK with 6 French sockets, with RCD

REF. **F2036/14**



BASIC INFORMATION

DESCRIPTION

Manufactured with high-quality aluminum, the profile has been specially designed to withstand the high temperatures inside rack cabinets. The Electroblock's mounting flaps allow for multiple fixing positions within the rack, optimizing its internal space. The Electroblock is supplied pre-wired internally, with an instruction manual, and includes mounting brackets for the rack cabinet. It is designed to power any electrical or electronic device housed inside the rack cabinet: hubs, switches, repeaters, routers, etc. It measures 1U in height (44.45 mm) to maximize space inside the cabinet and ensure compliance with IEC 60297 standards. The Electroblock is supplied pre-wired internally, with an instruction manual, and includes mounting brackets for the rack cabinet.

MATERIAL

Aluminium

COMPATIBILITY

19" Racks

ETIM CLASS

EC000330

TECHNICAL INFORMATION

CABLE SECTION ADMITTED (MM)
Up to 25 mm

FORMAT
DIN

BREAKING CAPACITY (A)
10000 A (with upstream fuse)

CURRENT (A)
25 A / 30 mA

LOGISTICS INFORMATION

UNITARY EAN CODE
8426436025707

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
2750000

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
0.86

PRODUCT NET WEIGHT
0.86

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8426436025707

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
55

PACKAGING WIDTH
500

PACKAGING LENGTH
100

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
2750000

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.86

PACKAGING NET WEIGHT
0.86

PACKAGING WEIGHT UNIT
KGM