

## Rocker for single-pole switching mechanisms for 1 element white Simon K45

REF. K109/9



## BASIC INFORMATION

### DESCRIPTION

In the series Simon K45, we find the rocker for single-pole switching mechanisms. With a white finish, in its individual version is presented in a single element, with the reference K109 / 9. It is not possible to combine 2 narrow rocker for control mechanisms with in a adaptor plate of the Simon 500 Cima series or of the series Simon K45. The installation can be perform in any universal recessed box, and in surface-mounted. It is manufactured in halogen-free thermoplastic, guarantees the no-propagation spread in case of fire, and low toxicity in the event of smoke generation. It measures 45x22.5, with a depth of 10mm.

### FINISH

White

### MATERIAL

Plastic

### COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-030)

### PACKAGING CONTENTS

Rocker and installation manual

### ETIM CLASS

EC000011

### REMARKS

It is not possible to combine 2 narrow button control mechanisms on a Simon 500 Cima-Simon K45 adapter plate

## TECHNICAL INFORMATION

### AVAILABLE MARKET

CE

### IP RATING

IP20

### TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60° C

### AVAILABLE IN

Quarter and half module versions

### KIT AVAILABILITY

No

### NUMBER OF MODULES

Four

### MAX TEMP DURING CONSTRUCTION WORK (°C)

+60° C

### MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

### RAL

9003

### INDICATOR FUNCTION

No

### VERSION

Single

## INSTALLATION AND MAINTENANCE

### REMOVAL OF COVER

Only with tool

### TYPE OF FASTENING

Fixing by direct snap-fit, no tools needed

### INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-030)

### INSTALLATION DIRECTION

Vertical according to the direction of the mechanisms

### INSTALLATION TYPE

Suitable for surface and flush mounting

## REGULATIONS

### REGULATIONS

Directive 2014/35/UE LVD + Directive 2011/65/UE RoHS + EN 50581:2012 + EN 60669-1:1999 + EN 60669-1:1999 A1:2002 + EN 60669-1:1999 A2:2008

## LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.006

PACKAGING MEASUREMENT  
UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT  
UNIT

KGM

PACKAGING VOLUME

544320

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8426436047006

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

544320

UNITS CONTAINED PACKAGING

10

PACKAGING GROSS WEIGHT

0.065

UNITARY PACKAGING VOLUME  
UNIT

MMQ

PACKAGING HEIGHT

72

PACKAGING NET WEIGHT

0.06

UNITARY PACKAGING GROSS  
WEIGHT

0.006

PACKAGING WIDTH

72

PACKAGING WEIGHT UNIT

KGM

PACKAGING LENGTH

105