

**Customisable kit with dual opening cover and fins, 10
schuko socket outlets and 2 empty elements white S400
Indesk Duo**

REF. 47605000-130



BASIC INFORMATION

DESCRIPTION

Thanks to its manual elevation system, this kit within the table customizable with fins and cover for 2 opening, 10 SCHUKOS and 2 empty elements white colour of the series Simon 400 Indesk Duo, is perfectly integrated where it is installed. We must be taken into account that for a correct installation, it is necessary to the use of the functions of the same version. Simon is a reference worldwide in the low voltage electrical equipment thanks to its constant research and development, this piece is a clear example of the effort made to find solutions for all kinds of environments, a kit where the enclosure is made of painted steel and a profile in anodised aluminium. For rockers and fastenings Simon choose the self-extinguishing thermoplastic insulation, which guarantees the creation of fire and prevents the emergence of fumes toxic. This piece is made to a voltage of 250 volts and a current of 16 amps.

FINISH

White

MATERIAL

Metal

COMPATIBILITY

Functions of the Simon 400 range, combinable with the Simon Electric Cabling range.

PACKAGING CONTENTS

Pre-wired profiles, enclosure, fastening claws, 3-pole T-branching with 1 male input and 2 female outputs and installation manual.

ETIM CLASS

EC002759

REMARKS

To complete the product installation combine it with the Simon 400 functions (refs. 400XXXXX-03X).

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

PROTECTION AGAINST DIRECT ACCESS OF CONTACTS

No

PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS

Yes, thanks to the included protective cover and cable outlet with metal fin

DIELECTRIC STRENGTH

No holes or contours, with 2000V at 50 Hz for 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60  C

NUMBER OF POSSIBLE ELEMENTS

2

FORMAT

Schuko

HEAT RESISTANCE (°C)

+70°C (according to standard IEC 60670)

INSULATION RESISTANCE (V-MΩ)

>5 MΩ at 500 V

CURRENT (A)

16 A

IP RATING

IP30

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 at +60  C

TYPE OF POWER SUPPLY CONNECTOR

Wieland  GST 18i male 3-pole overhead connector with 22 cm patch cord

RAL

9016

NUMBER OF REAR ENTRANCES

2

RECESS DIMENSION (MM)

318 x 175 mm (± 2mm)

NUMBER OF SOCKETS

10 sockets for standard current circuit

VERSION

12 elements

VOLTAGE (V~)

250 V~

INSTALLATION AND MAINTENANCE

CABLING ACCESS

With metal fin

CLAW RANGE OF OPERATION (MM)

Between 20 and 40 mm

REMOVAL OF COMPONENTS

NUMBER OF COVER OPENING POSITIONS

2

EXTINGUISHING (°C)

+70 °C (according to standard IEC 60670)

TYPE OF FASTENING

By lateral tightening of claws provided with the enclosure.

Optional possibility to fasten the enclosure with screws through the provided holes in the sides of the enclosure chassis.

REMOVAL OF THE FRAME

Only with tool

INSTALLATION TYPE

Suitable for recessed mount in furniture.

OPENING ORIENTATION

At 45° and 135°

REMOVAL OF THE PLATE

Only with tool

SECURING POSSIBILITIES

Using supplied claws or screws in the available holes

MOUNTING WITHOUT ACCESSORIES

Supplied with all necessary materials for installation.

REGULATIONS

REGULATIONS

Directiva 2014/35/UE LVD; Directiva 2011/65/UE RoHS; EN 50581:2012; EN 60670-1:2005; EN 60670-1:2005 A1:2013; IEC 60884-1 Ed 3.2;

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053197561

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

3.5

PRODUCT NET WEIGHT

3.5

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053197561

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

370

PACKAGING WIDTH

135

PACKAGING LENGTH

200

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

9990000

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

3.5

PACKAGING WEIGHT UNIT

KGM