MD-12 270º PIR+LUX BT Mesh wall surface On/Off white IP54

REF. **89202143-430**



BASIC INFORMATION

DESCRIPTION

Wall-mounted PIR motion and light-level detector. Recommended installation height is 2 m, with a maximum height of 6 m. It has a detection angle of 270º. The tangential detection range is 12.5 m and the radial detection range is 2.7 m.
The light-level adjustment range is 2 - 2000 lux and the timing range is 5 s - 60 min. The detector is configured via a Bluetooth app. It has a TEACH operating mode. Sensors can be interconnected via Bluetooth.
The control output is On/Off and the maximum switching power is 2000 W.
Supply voltage is 220 - 240 VAC. Detector operating temperature: -20 - 40 ºC.
White finish, IP 54 protection rating and dimensions: 87 x 82 x 98 mm.
5-year warranty.

For more product information, visit the STEINEL website by clicking here

FINISH

White

COMPATIBLE WITH MECHANICAL PUSH BUTTON

No

TECHNICAL INFORMATION

FREQUENCY
50 - 60 Hz

MAXIMUM POWER (W)
2000

RAL
9010

IP RATING
IP54

POWER SUPPLY (V~)
220/240 V~

CONTROL
On/Off

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION HEIGHT
1.8

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053462843

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING MEASUREMENT UNIT
MMT

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
0.25

PRODUCT NET WEIGHT
0.17

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053462843

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
155

PACKAGING WIDTH
90

PACKAGING LENGTH
75

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
1046250

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.25

PACKAGING NET WEIGHT
0.17

PACKAGING WEIGHT UNIT
KGM