Downlight 703.24 Square Orientable WW Wide Flood White

REF. **70324030-483**



BASIC INFORMATION

APPLICATION

Hotel,Restaurants,Residential,Retail,Office,Healthcare,Education

PACKAGING CONTENTS

1 Unit

ETIM CLASS

EC001744

TECHNICAL INFORMATION

FREQUENCY
50 - 60 Hz

CUT OFF
Yes

LUMENS/W
700 lm/7.5 W

IP RATING
IP20

DRIVER INCLUDED
Yes

OPTICS
Wide Flood

OPERATING TEMPERATURE RANGE (°C)
15 - 35 °C

L70 (°C)
30,000 h at 25 °C

PHOTOBIOLOGICAL CLASSIFICATION
Exempt category

POWER SUPPLY (V~)
230 V~

LIGHT BEAM APERTURE ANGLE (°)
40°

POWER (W)
7.5 W

COLOR TEMPERATURE (K)
3000 K

COLOR TYPE
WW

SERVICE LIFE
30.000 h

CONTROL
On/Off

LIGHTING EFFICIENCY (LM/W)
94 lm/W

CRI
80

LUMENS (LM)
700 lm

CHROMATICS CRI ICONS



INSTALLATION AND MAINTENANCE

INSTALLATION TYPE
Flush-mount

REGULATIONS

WARRANTY
3 years

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053089071

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
0.32

PRODUCT NET WEIGHT
0.2

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053089071

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
110

PACKAGING WIDTH
135

PACKAGING LENGTH
170

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
2524500

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.32

PACKAGING NET WEIGHT
0.2

PACKAGING WEIGHT UNIT
KGM