

Flat voice and data plate with dust cover for 1 RJ45 BeldenCDT® for 1 element aluminium Simon 500 Cima

REF. 50013085-033



BASIC INFORMATION

DESCRIPTION

Composed of 1 element for 1 RJ45 BeldenCDT®, our flat base plate of voice and data flat plate with dust cover in aluminium finishes, the, it is part of the Simon 500 Cima series. It has measures of 50x50x11 mm and a thickness of 11 mm. Its manufacture in halogen-free thermoplastic guarantees that there are no flame spread in case of fire is a notional case of fire and low toxicity very break loose any smoke. Finally, our plate includes clips for its set it in vertical and horizontal enclosures without the need of any adapter. And it is that, thanks to the use of the most advanced materials of the market, the Simon 500 Cima series possible to offer the best and safest mechanisms for your home, all under the support of a great brand.

FINISH

Aluminium

PACKAGING CONTENTS

Flat voice and data plate with dust cover

ETIM CLASS

EC000018

COMPATIBILITY

Simon 500 Cima enclosures

REMARKS

The plate is snap-fitted for mounting in vertical and horizontal enclosures without the need for an adaptor.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

DUST SHUTTER

Yes

NUMBER OF MODULES

1

AVAILABLE IN

Plate for 1 and 2 RJ45

FORMAT

RJ45

PLATE TYPE

Flat

COMPATIBLE WITH CONNECTORS

BeldenCDT® GigaFlex MDVO.

IP RATING

IP20

RJ45 ADAPTOR MODULE

Included in voice and data plate

RJ45 CONNECTORS

Not included in voice and data plate

KIT AVAILABILITY

No

SNAP-FIT RJ45 PLATES

BeldenCDT® RJ45 connectors

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60 °C

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

SNAP-FIT TYPE

BeldenCDT® RJ45 connectors

DUST PROTECTION

Yes

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60 °C

VERSION

Single

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Specific Simon 500 Cima

INSTALLATION DIRECTION

Vertical, corresponding with the direction of the mechanisms

INSTALLATION TYPE

Fixing by direct snap-fit, no tools needed.

REMOVAL OF THE PLATE

Only with tool

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8421053096734

PACKAGING VOLUME

0.604

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

10

PACKAGING VOLUME UNIT

DMQ

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

54

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING GROSS
WEIGHT

0.015

PACKAGING WIDTH

52

PACKAGING NET WEIGHT

0.15

PRODUCT NET WEIGHT

0.015

PACKAGING LENGTH

215

PACKAGING WEIGHT UNIT

KGM

