

POINT 56 MINI TW WIDE FLOOD DALI White

REF. 92061313-900



BASIC INFORMATION

DESCRIPTION

POINT Mini adjustable LED spotlight for three-phase track, white finish. Lens optic (Wide Flood 45°) with advanced light control, CRI>90, 4000K, 13.5W, 1200lm, 89 lm/W. Compact aluminium body (Ø56 mm y longitud de 82 mm), DALI-2 driver, flicker-free. Ideal for retail, displays and exhibitions.

FINISH

White

APPLICATION

Domestic, Office, Retail, Hotel, Contract

MATERIAL

Aluminium

ETIM CLASS

EC001744

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

IP RATING

IP20

NOMINAL VOLTAGE (V~)

220/240 V~

OPERATING TEMPERATURE RANGE (°C)

0...+35

POWER SUPPLY (V~)

220/240 V~

CONTROL

DALI2

COLOR TYPE

BIO

OPTICS

Wide Flood

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053401453

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

0.58

PRODUCT NET WEIGHT

0.4

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053401453

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

82

PACKAGING WIDTH

176

PACKAGING LENGTH

284

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

4452120

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.58

PACKAGING NET WEIGHT

0.4

PACKAGING WEIGHT UNIT

KGM