

2-way switch with key 2.5A 250V~ with 3 positions (key removable in rest position) welding terminal connection white Simon 27 Play

REF. 27523-65



BASIC INFORMATION

DESCRIPTION

2-way switch with key 3 positions (that is removable in rest position) and welding terminal connection, 2.5 A current and a voltage of 250V, belonging to the Simon 27 Play series. It measures 45x45mm and is manufactured with metal components with halogen-free insulation and thermoplastic trim, following the standards EN 61058-1: 2002 + A2: 2008 + EN 50581: 2012. This 2-way switch supports a cable section of 0,5mm, with a stripping of 7 mm and it can be installed both recessed and surface-mounted ideal in places with a temperature of between 5 and 40°C, although it is also true that can withstand extreme temperatures of -25 to 50°C, approximately. The cleaning of this 2-way switch is quite simple, just wipe it with a soft, dry cloth and will be fully shine, without the need to use never abrasive cloths or cleaners containing chlorine.

FINISH

White

COMPATIBILITY

Simon 27 Play, Simon 27 Neos, Simon 27 Scudo, Simon 27, Simon 27 Centralisations and Simon 44 Aqua frames

PACKAGING CONTENTS

Mechanism with cover

ETIM CLASS

EC001590

REMARKS

Mechanism with 2 positions and removable key in rest position.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

IP RATING

IP20

OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

CABLE SECTION ADMITTED (MM)

0,5 mm

KEY-REMOVAL POSITION

Standby

STORAGE TEMPERATURE RANGE (°C)

-25 - 50 °C

NUMBER OF POSSIBLE ELEMENTS

1 element

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

VERSION

Single

INDICATOR FUNCTION

No

TYPE OF MECHANISM

Key

VOLTAGE (V~)

250 V~

CURRENT (A)

2,5 A

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

7

CLAW

Included

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, American and
Centralisations

INSTALLATION TYPE

Suitable for surface and flush
mounting

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Welding

REGULATIONS

REGULATIONS

Dir. 2014/35/UE LVD | Dir. 2011/65/UE RoHS + post. mod. | EN IEC 61058-1:2018 | EN 61058-1-1:2016 | EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053082157

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8421053082157

PACKAGING VOLUME

0.598

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

DMQ

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

81

PACKAGING GROSS WEIGHT

0.095

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

82

PACKAGING NET WEIGHT

0.095

UNITARY PACKAGING GROSS
WEIGHT

0.095

PACKAGING LENGTH

90

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

0.095