LOOP wall-mounted luminaire DALI 3000 K White

REF. **91223354-300**

BASIC INFORMATION

BODY MATERIAL
Die-cast aluminium

PACKAGING CONTENTS
1 Unit

APPLICATION
Domestic,Office,Retail,Hotel,Contract

PACKAGING DIMENSIONS (MM)
116x224x171 mm

TECHNICAL INFORMATION

FREQUENCY
50 - 60 Hz

IP RATING
IP20

OPERATING TEMPERATURE RANGE (ºC)
0 - 35 ºC

POWER SUPPLY (V~)
110/240 V~

RAL
9016

COLOR TEMPERATURE (K)
3000 K

CONTROL
DALI

CRI
80

DIRECTIONAL
Yes

DRIVER INCLUDED
Yes

ELECTRICAL CLASS
II

ENERGY EFFICIENCY
A+

L70 (ºC)
20000h at 25ºC

LIGHT BEAM APERTURE ANGLE (°)
112º

COLOR TYPE
NW

LIGHTING EFFICIENCY (LM/W)
hasta 18 lm/W

LUMENS (LM)
77 lm

NUMBER OF LUMINAIRES
1

MACADAM STEPS
<3 Step MacAdam

OPTICS
General 112º

POWER FACTOR (Φ)
> 0,9

POWER (W)
4.5 W

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE
Trimless

REGULATIONS

EAC MARKED
Yes

ECORRAE MARKED
No

WARRANTY
3 years

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
0.6

PRODUCT NET WEIGHT
0.35

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8436547041862

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
116

PACKAGING WIDTH
171

PACKAGING LENGTH
224

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
4627350

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.39

PACKAGING NET WEIGHT
0.35

PACKAGING WEIGHT UNIT
KGM