

3RCA connector female with trim plate aluminium Simon K45

REF. K105B/8



BASIC INFORMATION

DESCRIPTION

Especially suitable for installation in meeting rooms, doctors mixtures, etc., the 3RCA connector, female, K45, is suitable for transmission both audio and video thanks to its 3 connectors: Red (audio right), audio yellow (left) and white or black (video). With trim plate and finished in Aluminium, it can be installed in surface-mounted or recessed, with screw terminal connection. The 3RCA connector together with the trim plate, support a maximum length of cabling 20 meters and a cable section from 0.2 to 0.5 mm. Manufactured with thermoplastic materials and self-extinguishing halogen-free, protects your room of the flame spread and toxicity smoke in case of fire, reaching a maximum temperature of between -25 and 50°C. Thanks to its 3RCA connector with trim plate, Simon K45, gives you the maximum functionality to make it work area has the best quality multimedia connections.

FINISH

Aluminium

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-033)

PACKAGING CONTENTS

Female 3RCA connector, cable fixing clamp and instruction sheet

ETIM CLASS

EC000018

REMARKS

Maximum wire length recommended; 20 meters For additional information, please read the product instruction sheet

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

CABLE SECTION ADMITTED (MM)

From 0,2 to 0,5 mm

CONNECTOR TYPE

RCA

NUMBER OF CONTACTS

9

NUMBER OF POSSIBLE ELEMENTS

1/2 element

FORMAT

RCA

IP RATING

IP20

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

STORAGE TEMPERATURE RANGE (°C)

-25 - 50 °C

VERSION

Single

NUMBER OF WIRES

9

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-033)

INSTALLATION TYPE

Suitable for surface and flush mounting

REGULATIONS

REGULATIONS

Dir. 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY EAN CODE

8426436064713

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8426436064713

PACKAGING VOLUME

0.012

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

HLT

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

50

PACKAGING GROSS WEIGHT

0.023

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

42

PACKAGING NET WEIGHT

0.023

UNITARY PACKAGING GROSS
WEIGHT

0.023

PACKAGING LENGTH

50

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

0.023