

Downlight white 735.21 NW Extensive 1-10V

REF. 73521130-784



BASIC INFORMATION

DESCRIPTION

The range Downlight 735, the Company Simon, whose light distribution is only with LED, it offers the best results of indoor lighting, specifically for each need. Its internal structure is based on a reflector with high reflectance, it sends the light towards the bottom with an angle of 85 ° of aluminium while the diffuser creates a soft lighting effect. There is no visual effect alteration of derived of flashing, as it is used to control the rizo management of the signal, making it is inocua and does not affect the view in intensive use conditions. Indoor lighting. Downlight 735.21 NW Extensive 1-10V. Category B, K, 2500 lm / 24 W, > 50,000 h at 25 ° C. neutral colour temperature (NW). P Ara recess or position, place in the ceiling, surface-mounted using accessories. Section, square 230mm x 230 mm, height 110 mm 1-10 V DALI of System push-button switch conventional. Made in polycarbonate body and with aluminium heat sink. 1,300 kg, white finish. Exempt from photobiological safety.

APPLICATION

General technical lighting

PACKAGING CONTENTS

1 Unit

ETIM CLASS

EC001744

TECHNICAL INFORMATION

FREQUENCY

50 Hz

DRIVER INCLUDED

Yes

LIGHTING EFFICIENCY (LM/W)

105 lm/W

IP RATING

IP20

ELECTRICAL CLASS

type 1

LUMENS (LM)

2500 lm

OPERATING TEMPERATURE RANGE (°C)

35 °C maximum

INTEGRATED POWER SUPPLY

Yes

LUMENS/W

2500 lm/24W

POWER SUPPLY (V~)

220/240 V~

L70 (°C)

100,000 h at 25 °C

OPTICS

Extensive

COLOR TEMPERATURE (K)

4000 K

L90 (°C)

50,000 h at 25 °C

PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

CONTROL

1-10 V

LIGHT BEAM APERTURE ANGLE (°)

85°

POWER (W)

24 W

CRI

80

COLOR TYPE

NW

SERVICE LIFE

50.000 h

CHROMATICS CRI ICONS

CRI
80

INSTALLATION AND MAINTENANCE

INSTALLATION ALTERNATIVES

Ceiling surface mount

INSTALLATION TYPE

Flush mount

MINIMUM INSTALLATION HEIGHT

150

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Quick connector

REGULATIONS

WARRANTY

5 years 50,000 h

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053136225

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8421053136225

PACKAGING VOLUME

9811125

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

135

PACKAGING GROSS WEIGHT

1.6

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

285

PACKAGING NET WEIGHT

1.3

UNITARY PACKAGING GROSS
WEIGHT

1.6

PACKAGING LENGTH

255

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

1.3