VGA HD15 connector female with screw terminal connection system and built-in plate ivory Simon 27 Play

REF. **2700091-031**



BASIC INFORMATION

DESCRIPTION

VGA connector, female, with HD 15 screw terminal connection system and built-in plate, in ivory colour finish and belonging to the Simon 27 Play series. It works by insertion and is a connector suitable both for surface and flush mounting, in places with a temperature located between 5 and 40ºC, approximately, although it can withstand extreme temperatures of -25 to 50ºC, plus or minus. The maximum recommended length of cabling is 20 meters, with a cross-cable section from 0.2 to 0.5 mm and the stripping of 5 mm, it also its dimensions are 45 x 45 mm This connector is made of metal components with halogen-free insulation and thermoplastic trim, a material very easy to maintain, because only need to clean it with a soft cloth and slightly moistened in soapy water, without having to reach resorting to cloths or abrasive cleaners containing chlorine.

FINISH

Ivory

COMPATIBILITY

Simon 27 Play, Simon 27 Neos, Simon 27 Scudo, Simon 27, Simon 27 Centralisations and Simon 44 Aqua frames

PACKAGING CONTENTS

VGA HD15 female connector and instruction sheet

ETIM CLASS

EC000018

REMARKS

Recommended maximum cable length: 20 metres. For more information see the product instruction sheet.

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

CABLE SECTION ADMITTED (MM)
From 0,2 to 0,5 mm

NUMBER OF CONNECTORS
1

CONNECTOR TYPE
VGA

NUMBER OF CONTACTS
15

NUMBER OF POSSIBLE ELEMENTS
1 element

FORMAT
VGA

IP RATING
IP20

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TYPE OF MECHANISM
Insertion

OPERATING TEMPERATURE RANGE (°C)
5 - 40 °C

STORAGE TEMPERATURE RANGE (°C)
-25 - 50 °C

TYPE
HD15

VERSION
Single

NUMBER OF WIRES
10

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)
5

CLAW
Simon 27

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX
Universal, American and Centralisations

INSTALLATION TYPE
Suitable for surface and flush mounting

TYPE OF TERMINAL CONNECTION - FUNCTION 1
Screw

REGULATIONS

REGULATIONS
Directive 2011/65/UE RoHS + EN 50581:2012

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053090602

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
0.068

PRODUCT NET WEIGHT
0.068

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053090602

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
57

PACKAGING WIDTH
76

PACKAGING LENGTH
76

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
0.105

PACKAGING VOLUME UNIT
DMQ

PACKAGING GROSS WEIGHT
0.068

PACKAGING NET WEIGHT
0.068

PACKAGING WEIGHT UNIT
KGM