


Linear luminaire 5500 BT Mesh 31W 3000K with detector 24GHz 8m HF+LUX IP44

REF. 89393620-313



BASIC INFORMATION

DESCRIPTION

Luminaire with integrated HF detector and Bluetooth connectivity. Power is 31.0 W, luminous flux is 4149 lm and colour temperature is 3000 K. Maximum installation height is 4 m, surface-mounted. Detection range is 8 m and detection angle is 360°.

The light-level adjustment range is 2 - 2000 lux and the timing range is 5 s - 60 min. The luminaire is configured via a Bluetooth app. Luminaires can be interconnected via Bluetooth mesh.

Supply voltage is 220 - 240 VAC. Operating temperature: -20 - 40 °C.

Protection rating IP 44 and IK 07, dimensions: 1200 x 164 x 75 mm.

5-year warranty.

For more product information, visit the STEINEL website by clicking [here](#)

FINISH

White

COMPATIBLE WITH MECHANICAL PUSH BUTTON

No

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

POWER SUPPLY (V~)

220/240 V~

IP RATING

IP44

CONTROL

BT

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053465950

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8421053465950

PACKAGING VOLUME

12502950

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

107

PACKAGING GROSS WEIGHT

2.33

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

95

PACKAGING NET WEIGHT

1.92

UNITARY PACKAGING GROSS WEIGHT

2.11

PACKAGING LENGTH

1230

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

1.92