VGA HD15 connector female with screw terminal connection system and built-in plate graphite Simon 27 Play

REF. **2700091-038**



BASIC INFORMATION

DESCRIPTION

Connector in graphite colour VGA HD15 female, from the Simon 27 Play series, with screw terminal connection system and built-in plate. It works by insertion and can be installed both recessed and surface-mounted, located in rooms with a temperature between 5 and 40ºC, approximately, although it is able to withstand extreme temperatures of -25 to 50ºC. It measures 45 x 45 mm and it is manufactured with metallic components halogen-free and thermoplastic trim, a material very easy to clean: Just wipe it with a soft cloth and slightly moistened in soapy water, without having to use never abrasive cloths or cleaners containing chlorine, as they could damage it. It has 2 modules and the maximum recommended length of cabling is 20 meters, with a cross-section of 0.2 to 0.5 mm and the stripping of 5 mm, approximately.

FINISH

Graphite

COMPATIBILITY

Simon 27 Play, Simon 27 Neos, Simon 27 Scudo, Simon 27, Simon 27 Centralisations and Simon 44 Aqua frames

PACKAGING CONTENTS

VGA HD15 female connector and instruction sheet

ETIM CLASS

EC000018

REMARKS

Recommended maximum cable length: 20 metres. For more information see the product instruction sheet.

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

CABLE SECTION ADMITTED (MM)
From 0,2 to 0,5 mm

NUMBER OF CONNECTORS
1

CONNECTOR TYPE
VGA

NUMBER OF CONTACTS
15

NUMBER OF POSSIBLE ELEMENTS
1 element

FORMAT
VGA

IP RATING
IP20

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TYPE OF MECHANISM
Insertion

OPERATING TEMPERATURE RANGE (°C)
5 - 40 °C

STORAGE TEMPERATURE RANGE (°C)
-25 - 50 °C

TYPE
HD15

VERSION
Single

NUMBER OF WIRES
10

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)
5

CLAW
Simon 27

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX
Universal, American and Centralisations

INSTALLATION TYPE
Suitable for surface and flush mounting

TYPE OF TERMINAL CONNECTION - FUNCTION 1
Screw

REGULATIONS

REGULATIONS
Directive 2011/65/UE RoHS + EN 50581:2012

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053117699

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
0.05

PRODUCT NET WEIGHT
0.05

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053117699

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
60

PACKAGING WIDTH
75

PACKAGING LENGTH
75

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
337500

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0

PACKAGING NET WEIGHT
0.05

PACKAGING WEIGHT UNIT
KGM