

IP66 mechanism holder unit with safety lock and a British socket base stainless steel Simon K45

REF. KSE4/23/72



BASIC INFORMATION

DESCRIPTION

With the range update, its equivalent for the new version is the KFH140/72 reference.

FINISH

Stainless steel

MATERIAL

Stainless steel

ETIM CLASS

EC000024

TECHNICAL INFORMATION

HEAT RESISTANCE (°C)

+70°C (according to standard IEC 60670)

IP RATING

IP66

MAXIMUM LOAD (KG)

1000kg

INDICATOR FUNCTION

No

KIT AVAILABILITY

No

RECESS DIMENSION (MM)

145 x 145 mm en falso suelo

CURRENT (A)

16 A

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

VOLTAGE (V~)

250 V~

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

12

NUMBER OF COVER OPENING POSITIONS

1

EXTINGUISHING (°C)

+650 °C (according to standard IEC 60670)

CAN BE INSTALLED IN TRAY

Plástica

LOGISTICS INFORMATION

UNITARY EAN CODE

8426436045224

PRODUCT NET WEIGHT

0.42

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

1445213

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8426436045224

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING VOLUME

1445213

PACKAGING HEIGHT

77

PACKAGING NET WEIGHT

0.42

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING WIDTH

137

PACKAGING WEIGHT UNIT

KGM

UNITARY PACKAGING GROSS WEIGHT

0.42

PACKAGING LENGTH

137