

Modular luminaire 726 120x30 Low Glare CW DALI

REF. 72661333-685



BASIC INFORMATION

DESCRIPTION

Luminaire 726 modular 120 x 30 LowGlare, with LEDs in cold colour (CW). It has an electric control DALI and its optics is microprismatic. It is part of the series Simon 726 modular luminaires, indoor lighting specific for the highest quality is displayed in a beautiful finished in aluminium colour, perfect to be integrated into the decoration of any space. The temperature of the colour of this luminaire category B is 5000 K and has 3200 lumens. Its power is 39 W and its power supply 100-240 V: In addition, it has a frequency of 50 / 60 Hz, it is worth mentioning that can withstand very well low and high temperatures, ranging between -15 and + 40 degrees centigrade. The modular luminaire Simon weight 2,6 kilos and measures 1195 x 295 millimetres. To install it will only need to place it in false ceiling, allowing its hardware. This will extend the service life of this product lighting for interiors.

DIFFUSER MATERIAL

PMMA

PACKAGING CONTENTS

1 unit

APPLICATION

General lighting

ETIM CLASS

EC002892

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

DRIVER INCLUDED

Yes

LUMENS (LM)

3200 lm

IP RATING

IP20

ELECTRICAL CLASS

Type 2

LUMENS/W

3200 lm/39W

OPERATING TEMPERATURE RANGE (°C)

-15 - 40 °C

INTEGRATED POWER SUPPLY

No

OPTICS

Microprismatic

POWER SUPPLY (V~)

100/240 V~

L70 (°C)

30,000 h at 25 °C

PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

COLOR TEMPERATURE (K)

5000 K

LIGHT BEAM APERTURE ANGLE (°)

90°

POWER (W)

39 W

CONTROL

DALI

COLOR TYPE

CW

SERVICE LIFE

30.000 h

CRI

80

LIGHTING EFFICIENCY (LM/W)

82 lm/W

CHROMATICS CRI ICONS

CRI
80

INSTALLATION AND MAINTENANCE

INSTALLATION ALTERNATIVES

Plaster ceiling, surface mount, flush mount, concealed profile and suspended

MINIMUM INSTALLATION HEIGHT

250

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Screw

INSTALLATION TYPE

False ceiling, visible hardware

REGULATIONS

WARRANTY

3 years 30,000 h

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

3

PRODUCT NET WEIGHT

2.1

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053194164

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

1281

PACKAGING WIDTH

40

PACKAGING LENGTH

350

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

17934000

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

2.1