


Connector VGA HD15 + 3RCA

REF. 7500092-039



BASIC INFORMATION

COMPATIBILITY

Simon 75, Simon 82 Detail, Simon 82 Nature and Simon 82 frames

PACKAGING CONTENTS

VGA HD15 female connector + 3RCA and instruction sheet

ETIM CLASS

EC002906

REMARKS

Recommended maximum cable length: 20 metres. For more information see the product instruction sheet.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

CABLE SECTION ADMITTED (MM)

From 0,2 to 0,5 mm

CONNECTOR TYPE

VGA + 3RCA

NUMBER OF CONTACTS

15

NUMBER OF POSSIBLE ELEMENTS

1 element

IP RATING

IP20

TYPE OF MECHANISM

Insertion

OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

STORAGE TEMPERATURE RANGE (°C)

-25 - 50 °C

VERSION

Single

NUMBER OF WIRES

10

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

13

INSTALLATION TYPE

Suitable for surface and flush mounting

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Screw

REGULATIONS

REGULATIONS

No aplica

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053121559

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

0.076

PRODUCT NET WEIGHT

0.076

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053121559

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

57

PACKAGING WIDTH

76

PACKAGING LENGTH

76

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

329232

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

0.076

PACKAGING WEIGHT UNIT

KGM