

Voice and data flat plate without dust cover and 1 element with 1 RJ45 connector category 6 FTP white Simon K45

REF. K096F/9



BASIC INFORMATION

DESCRIPTION

The plate of voice and data flat plate with 1 element without dust cover with RJ45 connector category 6 FTP within the collection Simon K45 with a cloth tone snow white, it fits perfectly into the set of a reduced space. With an average number of modules, it is composed of metal materials with thermoplastic isolated, halogen-free, which prevents the flame spread and toxicity smoke in case of fire. The plate of K45 voice and data of Simon, which supports cabling 22-24 AWG and ports type Keystone I and II, requires the use of 90 ° positioner in case of combining the K45 flat base plate in vertical enclosures to orient her position in the appropriate. Suitable for installation in recessed or surface-mounted, the RJ45 connector is clipped directly onto the plate without the need of screws, reducing installation time and maximizing its functionality, quality, elegance and innovation in the entire range Simon K45.

FINISH

White

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-030)

PACKAGING CONTENTS

Flat voice and data plate without dust cover, RJ45 category 6 FTP connector and installation manual

ETIM CLASS

EC000018

REMARKS

When combining the voice and data plate in vertical housings (mini columns, columns, Teleblock, channels, mechanism holders, etc.) you must use the 90° positioner (ref. K66) to guide the plate into a vertical position.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

DUST PROTECTION

No

NUMBER OF MODULES

Half

CABLE SECTION ADMITTED (MM)

22-24 AWG wiring

DUST SHUTTER

No

PLATE TYPE

Flat

AVAILABLE IN

Plate with 1 and 2 RJ45 connectors

FORMAT

RJ45

RAL

9003

RJ45 CONNECTION

With insertion tool

IP RATING

IP20

RJ45 ADAPTOR MODULE

Included in voice and data plate

CONNECTOR CHARACTERISTICS

Category 6 FTP

KIT AVAILABILITY

No

SNAP-FIT RJ45 PLATES

Keystone I, II, ATT®/Avaya®

RJ45 CONNECTORS

Included in voice and data plate

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

SNAP-FIT TYPE

Keystone I, II, ATT®/Avaya®

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60° C

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60° C

VERSION

Single

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-030)

INSTALLATION DIRECTION

Vertical according to the direction of the mechanisms

INSTALLATION TYPE

Suitable for surface and flush mounting

REMOVAL OF THE PLATE

Only with tool

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.03

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

2115750

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8426436031982

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

211575

UNITS CONTAINED PACKAGING

10

PACKAGING GROSS WEIGHT

0.3

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING HEIGHT

65

PACKAGING NET WEIGHT

0.3

UNITARY PACKAGING GROSS WEIGHT

0.03

PACKAGING WIDTH

155

PACKAGING WEIGHT UNIT

KGM

PACKAGING LENGTH

210