

Triple Schuko socket outlet 16A 250V~ with safety device and quick terminal connection white K45

REF. K13/9



BASIC INFORMATION

FINISH

White

MATERIAL

Plastic

COMPATIBILITY

Simon K45 enclosures for installation on wall, floor, ceiling, and furniture, and Simon 500 Cima enclosures (requires combining with K45 to 500 Cima adapter ref. 50012088-030).

ETIM CLASS

EC000125

TECHNICAL INFORMATION

FORMAT

Schuko

IP RATING

IP20

RAL

9003

CURRENT (A)

16 A

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

VOLTAGE (V~)

250 V~

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

12

EXTINGUISHING (°C)

+850 °C / 30 seconds (GWFI in accordance with standard IEC 60695-10-2)

REMOVAL OF THE SOCKET

Only with tool

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Fast

REGULATIONS

REGULATIONS

Dir. 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | IEC 60884-1 Ed. 3.2 | UNE 20315-1-1:2017 | UNE 20315-1-2:2017 | DS 60884-2-D1:2023

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053354841

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.145

PRODUCT NET WEIGHT

0.133

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053311639

UNITS CONTAINED PACKAGING

4

PACKAGING HEIGHT

60

PACKAGING WIDTH

145

PACKAGING LENGTH

190

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

1653000

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.58

PACKAGING NET WEIGHT

0.532

PACKAGING WEIGHT UNIT

KGM