

**Adjustable floor box kit for concrete floor 4 elements with
1 double sockets and 2 plates with 1 RJ45 Cat.6A FTP
connector grey Simon 500 Cima**

REF. 52007201-030



BASIC INFORMATION

DESCRIPTION

From the Simon 500 Cima series comes this with adjustable floor box kit for concrete floor and 4 elements with 1 double socket and 2 plates with 1 RJ45 Cat.6A FTP connector. In the format French-Belgian socket and snap-fit RJ45 Keystone I, II, ATT ® / Avaya ®. Finished in grey, with 1 double socket for standard current circuit. When installing mounted, keep in mind that it has a click terminal connection (1 click ®). To complete a successful installation of this product, it must be combined with a plastic tray (reference 52052102-035). Optionally, we recommend combining it with the flush-mount trim cover (reference 52053102-035) in cases where you do not install the same floor covering. This kit is specially designed and designed for assembly in concrete floor, although it is also suitable for installation in raised floor. Manufactured with different metal materials that have properties self-extinguishing and halogen-free. In case of fire, you will get the maximum protection.

FINISH

Grey

COMPATIBILITY

Simon 500 CIMA mechanisms

MATERIAL

Plastic

ETIM CLASS

EC000024

REMARKS

To complete the installation of the product, it must be combined with a plastic tray (ref.52052102-035). Alternatively, it may be combined with flush-mount trim cover (ref.52053102-035) in cases where the same floor lining is not installed.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

PROTECTION AGAINST DIRECT ACCESS OF CONTACTS

Yes

NUMBER OF CLAMP-HOLDER HOLES

8

NUMBER OF CONNECTORS

2

CONNECTOR TYPE

6A FTP

DUST SHUTTER

Yes

FORMAT

French-Belgian

IK CLASSIFICATION

08

INDICATOR FUNCTION

Yes

CURRENT (A)

16 A

IP RATING

IP4X

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

PLATE TYPE

Flat

RAL

7011

RECESS DIMENSION (MM)

170 x 154 mm

VOLTAGE (V~)

250 V~

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

0

NUMBER OF COVER OPENING POSITIONS

2

EXTINGUISHING (°C)

+850 °C / 30 seconds (GWFI in accordance with standard IEC 60695-2-11)

REMOVAL OF THE FRAME

Only with tool

CAN BE INSTALLED IN TRAY

Plastic and metallic

INSTALLATION DIRECTION

Horizontal, Vertical

REMOVAL OF THE PLATE

Only with tool

REMOVAL OF THE SOCKET

Only with tool

TYPE OF TERMINAL CONNECTION - FUNCTION 1

1 click connection (1 click®)

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053112298

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

1.45

PRODUCT NET WEIGHT

1.45

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053112298

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

84

PACKAGING WIDTH

181

PACKAGING LENGTH

212

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

3223248

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

1.45

PACKAGING WEIGHT UNIT

KGM