

Downlight 706.21 Flush mount WW Flood Aluminium

REF. 70621033-383



BASIC INFORMATION

DESCRIPTION

Finished in aluminium, the Downlight 706.21 flush-mounted of the collection Simon puts at your disposal a lighting sustainable and quality with a minimalist design that is integrated into all types of spaces centres or office. For a larger light beam, with a optics FLOOD photometric distribution, linked to its colour temperature of 3100 K and a lighting ambience warm WW, make it the perfect to create an ambience light comfortable, in addition to the energy savings provided by LED lighting, it has a performance of 900 lm with total consumption of 15 W and compatibility with power supplies of 10-240 Volts and 50-60 Hertz rate. Includes control system, switching on ON-OFF whose quantity (QTY.) of switching on and off do not have influence on the service life of the luminaire, which reaches the 30,000 hours at an average temperature of 25 ° C and can reach a maximum of 40 °C.

APPLICATION

Ambient lighting

PACKAGING CONTENTS

1 unit

ETIM CLASS

EC001744

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

DRIVER INCLUDED

Yes

LUMENS/W

900 lm/15W

IP RATING

IP44

ELECTRICAL CLASS

Type 2

OPTICS

Flood

OPERATING TEMPERATURE RANGE (°C)

40 °C maximum

INTEGRATED POWER SUPPLY

No

PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

POWER SUPPLY (V~)

100/240 V~

L70 (°C)

30,000 h at 25 °C

POWER (W)

15 W

COLOR TEMPERATURE (K)

3100 K

COLOR TYPE

WW

POWER SUPPLY DIMENSIONS (MM)

45x141x26 mm

CONTROL

On/Off

LIGHTING EFFICIENCY (LM/W)

60 lm/W

SERVICE LIFE

30.000 h

CRI

80

LUMENS (LM)

900 lm

CHROMATICS CRI ICONS

CRI
80

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION HEIGHT

180

INSTALLATION TYPE

Flush mount

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Screw

REGULATIONS

WARRANTY

3 years 30,000 h

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

0.502

PRODUCT NET WEIGHT

0.502

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053122136

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

135

PACKAGING WIDTH

135

PACKAGING LENGTH

155

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

2.825

PACKAGING VOLUME UNIT

DMQ

PACKAGING GROSS WEIGHT

0.502

PACKAGING NET WEIGHT

0.502

PACKAGING WEIGHT UNIT

KGM