

## Waterproof luminaire 780 IP65 4000 K 1500 1-10 V

REF. 78032133-884



### BASIC INFORMATION

#### DESCRIPTION

The 780 waterproof luminaire, made with an extruded PC body, is perfect for lighting car parks, industries, underpasses, storage areas, humid spaces, etc. Its LED technology allows it to switch on instantly and avoid flickering. The luminaire is IP65 and IK08 rated and comes in 3 different sizes and versions with 1-10 V / DALI dimming.

#### APPLICATION

Car park lighting, Industrial lighting

#### PACKAGING CONTENTS

1 unit

#### ETIM CLASS

EC002892

## TECHNICAL INFORMATION

### FREQUENCY

50 - 60 Hz

### CRI

80

### LUMENS/W

5700 lm/50W

### IK CLASSIFICATION

08

### ELECTRICAL CLASS

Type 2

### OPTICS

General

### IP RATING

IP65

### L70 (°C)

50,000 h at 25°C

### PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

### OPERATING TEMPERATURE RANGE (°C)

-20 - 35 °C

### LIGHT BEAM APERTURE ANGLE (°)

120°

### POWER (W)

50 W

### POWER SUPPLY (V~)

220/240 V~

### COLOR TYPE

NW

### SERVICE LIFE

50.000 h

### COLOR TEMPERATURE (K)

4000 K

### LIGHTING EFFICIENCY (LM/W)

114 lm/W

### CONTROL

1-10 V

### LUMENS (LM)

5700 lm

### CHROMATICS CRI ICONS

CRI  
80

## INSTALLATION AND MAINTENANCE

### INSTALLATION TYPE

Surface-mounted / Wall /  
Suspended

## REGULATIONS

### WARRANTY

5 years 50.000 h

## LOGISTICS INFORMATION

### UNITARY PACKAGING HEIGHT

0

### UNITARY PACKAGING WIDTH

0

### UNITARY PACKAGING LENGTH

0

### UNITARY PACKAGING VOLUME

0

### UNITARY PACKAGING GROSS WEIGHT

1.438

### PRODUCT NET WEIGHT

1.12

### UNITARY PACKAGING WEIGHT UNIT

KGM

### PACKAGING EAN

8421053217221

### UNITS CONTAINED PACKAGING

1

### PACKAGING HEIGHT

1550

### PACKAGING WIDTH

64

### PACKAGING LENGTH

63

### PACKAGING MEASUREMENT UNIT

MMT

### PACKAGING VOLUME

6249600

### PACKAGING VOLUME UNIT

MMQ

### PACKAGING GROSS WEIGHT

1.438

### PACKAGING NET WEIGHT

1.12

### PACKAGING WEIGHT UNIT

KGM