

Modular luminaire Clean room 120x30 4000K

REF. 75511330-394



BASIC INFORMATION

DESCRIPTION

Sealed LED luminaire 755 (1195x295mm) with multilayer front (microprismatic diffuser + tempered glass) for demanding environments. CRI90, 4000K, UGR<19. DALI-2 driver with energy report and diagnostics. IP65, IK08. Power 45W, output 4550lm, efficiency 101 lm/W. Perfect for hospitals, labs, clean rooms. Complies with UNE EN ISO 14644 Class 1.

FINISH

White

APPLICATION

Healthcare

MATERIAL

Aluminium

ETIM CLASS

EC002892

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

IK CLASSIFICATION

08

IP RATING

IP65

OPERATING TEMPERATURE RANGE (°C)

0...+35

POWER SUPPLY (V~)

220/240 V~

CONTROL

DALI2

COLOR TYPE

NW

OPTICS

Diffused

REGULATIONS

REGULATIONS

Dir. 2014/30/UE EMC | Dir. 2014/35/UE LVD | Dir. 2009/125/EC ErP (Reg. UE 2019/2015) | Dir. 2009/125/EC ErP (Reg. UE 2019/2020) | Dir. 2011/65/UE RoHS + post. mod | EN IEC 60598-2-2:2023 used in conjunction IEC 60598-1:2020 | EN IEC 55015:2019 + A11:2020 | EN 60598-2-25:1994 + A1:2004 | EN IEC 61547:2023 | EN 62493:2015 | EN IEC 61000-3-2:2019 + A1:2021*1 | EN 62717:2017 + A2:2019 | EN 61000-3-3:2013 + A1:2019 + A2:2021 | EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053360071

UNITARY PACKAGING GROSS
WEIGHT

0.19

PACKAGING LENGTH

0

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.07

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING VOLUME

0

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8421053360071

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING
MEASUREMENT UNIT

MMT

UNITS CONTAINED PACKAGING

1

PACKAGING GROSS WEIGHT

0.19

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

0

PACKAGING NET WEIGHT

0.07

UNITARY PACKAGING VOLUME
UNIT

MMQ

PACKAGING WIDTH

0

PACKAGING WEIGHT UNIT

KGM