Charger 2x2.1A 5V DC type A USB port white Simon K45

REF. **K126E/9**



BASIC INFORMATION

FINISH
White

MATERIAL
Thermoplastic

COMPATIBILITY
Simon K45 enclosure for mounting on the wall, floor, ceiling and furniture. Not compatible with Simon 500 Cima enclosures (for this, use ref. 2701097-030 and the S27 to Simon 500 Cima adaptor, ref. 50011088-030)

PACKAGING CONTENTS
Double USB charger, trim cover and installation manual

ETIM CLASS
EC002949

REMARKS
Allows simultaneous charging of up to two devices connected through USB Type A connectors, in which case the maximum intensity (2.1A) will be shared between the two connections.

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

CABLE SECTION ADMITTED (MM)
From 1,0 to 2,5 mm

NUMBER OF CONNECTORS
2

CONNECTOR TYPE
USB A

NUMBER OF CONTACTS
2

FORMAT
USB A

CURRENT (A)

IP RATING
IP20

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TYPE OF MECHANISM
Insertion

NOMINAL VOLTAGE (V~)
230 V~

POWER SUPPLY (V~)
230 V~

RAL
9003

RECESS DIMENSION (MM)
40

USB CHARACTERISTICS
10W

USB CURRENT (A)
2,1 A

USB VOLTAGE (V~)
5 Vdc

VERSION
Double

NUMBER OF WIRES
2

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)
10

REMOVAL OF CONNECTOR
Only with tool

EXTINGUISHING (°C)
+850 °C / 30 seconds (GWFI in accordance with standard IEC 60695-10-2)

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX
Universal and specific Simon K45.

INSTALLATION DIRECTION
Horizontal, Vertical

INSTALLATION TYPE
Suitable for surface and flush mounting

TYPE OF TERMINAL CONNECTION - FUNCTION 1
Screw

TYPE OF TERMINAL CONNECTION - FUNCTION 2
Screw

REGULATIONS

REGULATIONS

Dir. 2014/35/UE LVD | Dir. 2011/65/UE RoHS + post. mod. | Dir. 2014/30/UE EMC | Dir. 2009/125/EC ErP (Reg. UE 2019/1782) | EN IEC 61000-3-2:2019 + A1:2021 + A2:2024 | EN 50563:2011 + A1:2013 | EN 61000-3-3:2013 + A1:2019 + A2:2021 EN IEC 62368-1:2020 + A11:2020 | EN 50563:2011 + A1:2013 | EN IEC 61000-6-1:2019 | EN IEC 63000:2018 | EN IEC 61000-6-3:2021

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053198766

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
0.069

PRODUCT NET WEIGHT
0.069

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053198766

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
55

PACKAGING WIDTH
65

PACKAGING LENGTH
65

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
232375

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0

PACKAGING NET WEIGHT
0.069

PACKAGING WEIGHT UNIT
KGM