

LED status indicator for double socket outlet Simon 500 Cima

REF. 50000802-039



BASIC INFORMATION

DESCRIPTION

LED status indicator for double socket outlet of the series Simon 500 Cima. A series of that stands out for its adaptability to the new trends in decoration. Its dimensions are 23 x 9 x 20 mm and it is manufactured with metallic components with self-extinguishing thermoplastic insulation and halogen-free; guarantees no flame propagation in case of fire and low toxicity in the event of smoke generation. It has a detailed in graphite finish and is compatible with Schuko double socket outlets of Simon 500 Cima. Combined with the required cover for double socket outlets with viewer. And is also suitable for combining in double socket outlets surface-mounted or flush-mounted To clean it, you need to be taken into account, you must do always with a soft and dry cloth, never use cloths or abrasive cleaners containing chlorine, as they may damage the piece.

FINISH

Graphite

MATERIAL

Various

COMPATIBILITY

German double socket outlets
Simon 500 Cima

PACKAGING CONTENTS

LED status indicator for double
socket outlet Simon 500 Cima
and installation manual

ETIM CLASS

EC002649

REMARKS

This article is only compatible with the Simon 500 Cima German double socket outlets. Must be combined with the cover for double socket outlets with viewer.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60 °C in surface-mount wall
installation and +90 °C in flush-
mount wall installation

INDICATOR FUNCTION

Yes

IP RATING

IP20

KIT AVAILABILITY

Yes

LED CONSUMPTION INDICATOR (MA)

0.55

MAINTENANCE

Clean with a soft, dry cloth. Do
not use abrasive cloths or
cleaning products that contain
chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60 °C

VERSION

2 elements

INSTALLATION AND MAINTENANCE

TYPE OF FASTENING

By direct snap-fit in the housing of the German double socket outlet provided for that purpose (no tools needed for fastening))

INSTALLATION DIRECTION

Vertical, corresponding with the direction of the mechanisms

INSTALLATION TYPE

Suitable for combining in flush or surface-mount double socket outlets

REGULATIONS

REGULATIONS

UNE 20.315 / EN 60.998-2-3

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8421053093689

PACKAGING VOLUME

0.677

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

10

PACKAGING VOLUME UNIT

DMQ

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

92

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING GROSS WEIGHT

0.011

PACKAGING WIDTH

92

PACKAGING NET WEIGHT

0.11

PRODUCT NET WEIGHT

0.011

PACKAGING LENGTH

110

PACKAGING WEIGHT UNIT

KGM

