

Downlight 709 Dip Switch DALI2 White

REF. 70921330-497



BASIC INFORMATION

DESCRIPTION

Recessed 84mm LED downlight 709 DALI-2 dimmable with white aluminium body and recessed design for reduced glare. Wide Flood 38° optics, tilt up to 28°, CRI>90 and CCT selector (2700K, 3000K, 4000K). Ideal for offices, hotels and retail. 79 lm/W efficiency and 30,000h lifetime.

FINISH

White

APPLICATION

General lighting

MATERIAL

Aluminium

ETIM CLASS

EC001744

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

OPERATING TEMPERATURE RANGE (°C)

-10...+35

POWER SUPPLY (V~)

220/240 V~

IP RATING

IP20

CONTROL

DALI2

REGULATIONS

REGULATIONS

Dir. 2014/35/UE LVD | Dir. 2014/30/UE EMC | Dir. 2009/125/EC ErP (Reg. UE 2019/2020) | Dir. 2009/125/EC ErP (Reg. UE 2019/2015) | Dir. 2011/65/UE RoHS + post. mod. | EN 60598-2-2:2012 | EN IEC 55015:2019 + A11:2020 | EN 62493:2015 | EN IEC 61547:2023 | EN 62717:2017 + A2:2019 | EN IEC 61000-3-2:2019 + A1:2021*1 | EN IEC 63000:2018 | EN 61000-3-3:2013 + A1:2019 + A2:2021

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053381991

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

0.48

PRODUCT NET WEIGHT

0.25

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053381991

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

120

PACKAGING WIDTH

130

PACKAGING LENGTH

130

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

2028000

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.48

PACKAGING NET WEIGHT

0.25

PACKAGING WEIGHT UNIT

KGM