

## Complete flush-mounted in the desk kit with dual opening cover, metal fin, 4x USB charger, 6 German socket outlets and 4 empty elements aluminium Simon 400

REF. 47623000-133



### BASIC INFORMATION

#### FINISH

Aluminium

#### MATERIAL

Metal

#### COMPATIBILITY

Can be combined with the range of Electric Cabling from Simon.

#### PACKAGING CONTENTS

Pre-wired profiles, enclosure, fastening claws, 3-pole T-branching with 1 male input and 2 female outputs and installation manual.

## TECHNICAL INFORMATION

### AVAILABLE MARKET

CE

### PROTECTION AGAINST DIRECT ACCESS OF CONTACTS

No

### PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS

Yes, thanks to the included protective cover and cable outlet with metal fin

### DIELECTRIC STRENGTH

No holes or contours, with 2000V at 50 Hz for 1 minute

### MAX TEMP DURING CONSTRUCTION WORK (°C)

+60° C

### FORMAT

Schuko

### HEAT RESISTANCE (°C)

+70°C (according to standard IEC 60670)

### INSULATION RESISTANCE (V-MΩ)

>5 MΩ a 500 V

### CURRENT (A)

16 A

### IP RATING

IP30

### MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

### TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60° C

### NOMINAL VOLTAGE (V~)

250 V~

### TYPE OF POWER SUPPLY CONNECTOR

Wieland® GST 18i male 3-pole overhead connector with 22 cm patch cord

### RAL

9006

### NUMBER OF REAR ENTRANCES

4

### RECESS DIMENSION (MM)

318 x 175 mm (± 2mm)

### NUMBER OF SOCKETS

6 sockets for standard current circuit

### NUMBER OF USB CHARGERS

2

### VERSION

12 elements

## INSTALLATION AND MAINTENANCE

### CABLING ACCESS

With metal fin

### CLAW RANGE OF OPERATION (MM)

Between 20 and 40 mm

### NUMBER OF COVER OPENING POSITIONS

2

### EXTINGUISHING (°C)

+70 °C (according to standard IEC 60670)

### TYPE OF FASTENING

By tightening existing clamps in the fastening bracket.

### REMOVAL OF THE FRAME

Only with tool

### INSTALLATION TYPE

Suitable for recessed mount in furniture.

### OPENING ORIENTATION

At 45° and 135°

### SECURING POSSIBILITIES

Using supplied claws or screws in the available holes

### MOUNTING WITHOUT ACCESSORIES

Supplied with all necessary materials for installation.

## REGULATIONS

### REGULATIONS

Directiva 2014/35/UE LVD;Directiva 2011/65/UE RoHS;EN 50581:2012;EN 60670-1:2005;EN 60670-1:2005 A1:2013;IEC 60884-1 Ed 3.2;

## LOGISTICS INFORMATION

UNITARY EAN CODE

8421053273791

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING  
MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME  
UNIT

MMQ

UNITARY PACKAGING GROSS  
WEIGHT

3.5

PRODUCT NET WEIGHT

3.5

UNITARY PACKAGING WEIGHT  
UNIT

KGM

PACKAGING EAN

8421053273791

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

130

PACKAGING WIDTH

215

PACKAGING LENGTH

345

PACKAGING MEASUREMENT  
UNIT

MMT

PACKAGING VOLUME

9642750

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

3.5

PACKAGING WEIGHT UNIT

KGM