
Flat voice and data plate with dust cover for 1 element with 2 category 5e UTP RJ45 white Simon 500 Cima

REF. **50004089-030**



BASIC INFORMATION

DESCRIPTION

Flat base plate in white colour of the Simon 500 Cima series and that is used for data and voice and has a dust cover with 1 element and 2 RJ45 category 5e UTP of Keystone I, II, ATT ® / Avaya ®. It measures 50 x 50 x 32.5 mm and allows cabling 22-26 AWG. It is a plate that has been designed according to the regulation TIA 568 C. 2 and is manufactured with metal components with thermoplastic insulation, self-extinguishing and halogen-free. This material is perfect for both in case of fire and smoke, as it prevents propagate the fire and there is a high level of toxicity. For its installation you will not need any type of adapter, as this angled plate of the Simon 500 Cima range incorporates the clips required for fastening in horizontal and vertical enclosures, so that its installation is simple.

FINISH

White

COMPATIBILITY

Simon 500 Cima enclosures

PACKAGING CONTENTS

Flat voice and data plate with dust cover, 2 category 5e UTP RJ45 and installation manual

ETIM CLASS

EC000018

REMARKS

The plate is snap-fitted for mounting in vertical and horizontal enclosures without the need for an adaptor.

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

CABLE SECTION ADMITTED (MM)
22-26 AWG wiring

RJ45 CONNECTION
With insertion tool

CONNECTOR CHARACTERISTICS
Category 5e UTP

NUMBER OF CONNECTORS
2

RJ45 CONNECTORS
Included in voice and data plate

MAX TEMP DURING CONSTRUCTION WORK (°C)
+60 °C

DUST PROTECTION
Yes

FORMAT
RJ45

IP RATING
IP20

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)
-5 to 60 °C

NUMBER OF MODULES
1

PLATE TYPE
Flat

RAL
9003

RJ45 ADAPTOR MODULE
Included in voice and data plate

SNAP-FIT RJ45 PLATES
Keystone I, II, ATT®/Avaya®

SNAP-FIT TYPE
Keystone I, II, ATT®/Avaya®

VERSION
Single

INSTALLATION AND MAINTENANCE

REMOVAL OF CONNECTOR

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX
Specific Simon 500 Cima

INSTALLATION DIRECTION
Vertical, corresponding with the direction of the mechanisms

INSTALLATION TYPE
Fixing by direct snap-fit, no tools needed.

REMOVAL OF THE PLATE
Only with tool

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
0.037

PRODUCT NET WEIGHT
0.037

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053097922

UNITS CONTAINED PACKAGING
20

PACKAGING HEIGHT
80

PACKAGING WIDTH
224

PACKAGING LENGTH
290

PACKAGING MEASUREMENT UNIT
MMT


PACKAGING VOLUME
0.052

PACKAGING VOLUME UNIT
HLT

PACKAGING GROSS WEIGHT
0

PACKAGING NET WEIGHT
0.74

PACKAGING WEIGHT UNIT
KGM


50
50
5
11