

Flat voice and data plate with dust cover for 1 element with 1 category 5e UTP RJ45 graphite Simon 500 Cima

REF. 50004085-038



BASIC INFORMATION

DESCRIPTION

The daily use of the electronic devices have a direct relationship with the deterioration of its structure, to avoid this, we can make you in the flat plate for voice and data with dust cover for an element with a RJ45 connector category 5e UTP in graphite finish of the Simon 500 Cima series, an accessory with an innovative design that you can combine in all kinds of environments decorative. The resistance of this plate of voice and data, which includes clips for fastening in vertical and horizontal enclosures without the need for an adaptor, is due to the metal components with self-extinguishing and halogen-free thermoplastic insulation. with which it has been manufactured, its dimensions are 50 x 50 x 32.5 mm and a cabling 22-26 AWG. Also, this plate guarantees no flame propagation in case of fire and low toxicity in the event of smoke generation.

FINISH

Graphite

PACKAGING CONTENTS

Flat voice and data plate with dust cover, category 5e UTP RJ45 connector and installation manual

ETIM CLASS

EC000018

COMPATIBILITY

Simon 500 Cima enclosures

REMARKS

The plate is snap-fitted for mounting in vertical and horizontal enclosures without the need for an adaptor.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

DUST PROTECTION

Yes

PLATE TYPE

Flat

CABLE SECTION ADMITTED (MM)

22-26 AWG wiring

FORMAT

RJ45

RAL

7021

RJ45 CONNECTION

With insertion tool

IP RATING

IP20

RJ45 ADAPTOR MODULE

Included in voice and data plate

CONNECTOR CHARACTERISTICS

Category 5e UTP

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

SNAP-FIT RJ45 PLATES

Keystone I, II, ATT®/Avaya®

NUMBER OF CONNECTORS

1

SNAP-FIT TYPE

Keystone I, II, ATT®/Avaya®

RJ45 CONNECTORS

Included in voice and data plate

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60 °C

VERSION

Single

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60 °C

NUMBER OF MODULES

1

INSTALLATION AND MAINTENANCE

REMOVAL OF CONNECTOR

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Specific Simon 500 Cima

INSTALLATION DIRECTION

Vertical, corresponding with the direction of the mechanisms

INSTALLATION TYPE

Fixing by direct snap-fit, no tools needed.

REMOVAL OF THE PLATE

Only with tool

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

26

UNITARY PACKAGING GROSS WEIGHT

0.026

PACKAGING LENGTH

86

UNITARY PACKAGING WIDTH

58

PRODUCT NET WEIGHT

0.026

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING LENGTH

86

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

0.052

UNITARY PACKAGING MEASUREMENT UNIT

MMT

PACKAGING EAN

8421053098059

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

129688

UNITS CONTAINED PACKAGING

20

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING HEIGHT

26

PACKAGING NET WEIGHT

0.52

PACKAGING WIDTH

58

PACKAGING WEIGHT UNIT

KGM

