Front kit for 3 elements with 2 German socket outlets and 1 2xUSB charger gloss white Simon 100

REF. **10020308-130**



BASIC INFORMATION

DESCRIPTION

This front kit for 3 elements, with 2 Schuko plug bases (16 A) and with a double series USB charger has the following reference: 10020308-130 and an elegant glossy white finish. Its installation is very simple: it can be placed horizontally and vertically.

The type of emborning is by cut (1 click system) and for the USB part, by screw-type. The type of activation is by insertion and has dimensions of 225.5x83.5mm. This product is part of the Simon 100 range, so it is compatible with all the mechanisms in this series.

For proper maintenance and operation, it must be preserved in a temperature range of 5 to 40º C and a storage temperature range of -25 to 50º C.

This is a device that has been made based on the regulations: directive 2014/35 / UE LVD + directive 2014/30 / UE EMC + directive 2011/65 / UE RoHS + EN 50581: 2012 + EN 60950-1: 2006 + EN 60950-1: 2006 A11: 2009 + EN 60950-1: 2006 A1: 2010 + EN 60950-1: 2006 A12: 2011 + EN 60950-1: 2006 A2: 2011 * 3 + ETSI-EN 301489-34 v14 .1 * 3 + IEC 60884-1 Ed. 3.2 * 1 and is marketed in the EC.

FINISH

Gloss white

COMPATIBILITY

Kit mechanisms Simon 100

ETIM CLASS

EC000007

MATERIAL

Thermoplastic

PACKAGING CONTENTS

Mechanism and instructions

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

NUMBER OF POSSIBLE ELEMENTS
3 elements

FORMAT
Schuko,USB

INDICATOR FUNCTION
No

IP RATING
IP20

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

MONOBLOCK
Yes

OPERATING TEMPERATURE RANGE (°C)
5 - 40 °C

STORAGE TEMPERATURE RANGE (°C)
-25 - 50 °C

VERSION
3 elements

INSTALLATION AND MAINTENANCE

INSTALLATION DIRECTION
Vertical and horizontal

INSTALLATION TYPE
Suitable for flush mounting

REGULATIONS

REGULATIONS
Directive 2014/35/UE LVD + Directive 2014/30/UE EMC + Directive 2011/65/UE RoHS + EN 50581:2012 + EN 60950-1:2006 + EN 60950-1:2006 A11:2009 + EN 60950-1:2006 A1:2010 + EN 60950-1:2006 A12:2011 + EN 60950-1:2006 A2:2011*3 + ETSI-EN 301489-34 v14.1*3 + IEC 60884-1 Ed. 3.2*1

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053201589

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
0.13

PRODUCT NET WEIGHT
0.13

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053201589

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
25.3

PACKAGING WIDTH
226

PACKAGING LENGTH
84

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
480295.2

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0

PACKAGING NET WEIGHT
0.13

PACKAGING WEIGHT UNIT
KGM