

Projector 889 100W 5500K

REF. 88933038-885



BASIC INFORMATION

DESCRIPTION

Outdoor LED projector for window display and facade lighting, robust, adjustable, and designed for high performance in commercial applications. Available in different power ratings, the 889 outdoor projector allows you to select the appropriate model depending on the mounting height, the surface to be illuminated, and the desired impact level. Installation type: Surface. Optics: 110. Color temperature: 5500K. Power: 100W. Lumens: 9000lm. Efficiency: 90lm/w. Protection rating IP: IP65. Power supply: 220-240 V. 50/60 Hz. Dimensions: 256 mm x 229 mm x 42 mm.

APPLICATION

Wall lighting, Industrial
lighting, Commercial areas

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

IK CLASSIFICATION

05

IP RATING

IP65

OPERATING TEMPERATURE RANGE (°C)

-25...+50

POWER SUPPLY (V~)

220/240 V~

CONTROL

On/Off

LIGHTING EFFICIENCY (LM/W)

90 lm/W

LUMENS (LM)

9000 lm

OPTICS

Symmetric

POWER (W)

100 W

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE

Surface / Wall

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053440445

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

1.024

PRODUCT NET WEIGHT

0.97

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053440445

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

255

PACKAGING WIDTH

210

PACKAGING LENGTH

280

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

14994000

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

4.096

PACKAGING NET WEIGHT

0.97

PACKAGING WEIGHT UNIT

KGM