

Spotlight 880.33 industrial 3000 K SYM

REF. 88033038-173



BASIC INFORMATION

APPLICATION

Accent lighting, General lighting

PACKAGING CONTENTS

1 unit

ETIM CLASS

EC001744

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

CRI

70

LIGHTING EFFICIENCY (LM/W)

120,7 lm/W

IK CLASSIFICATION

08

DIRECTIONAL

Yes

LUMENS (LM)

18100 lm

IP RATING

IP65

DRIVER INCLUDED

Yes

LUMENS/W

18100lm/ 150W

OPERATING TEMPERATURE RANGE (°C)

40 °C maximum

L70 (°C)

100,000 h at 25 °C

OPTICS

Symmetric

POWER SUPPLY (V~)

100/240 V~

L90 (°C)

30,000 h at 25 °C

PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

COLOR TEMPERATURE (K)

3000 K

LIGHT BEAM APERTURE ANGLE (°)

90°

POWER (W)

150 W

CONTROL

On/Off

COLOR TYPE

WW

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE

Surface (with bracket)

REGULATIONS

WARRANTY

5 years

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053205501

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

7

PRODUCT NET WEIGHT

5.316

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053205501

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

130

PACKAGING WIDTH

515

PACKAGING LENGTH

435

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

29123250

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

7

PACKAGING NET WEIGHT

5.316

PACKAGING WEIGHT UNIT

KGM