

Complete table-top kit with 3 German socket outlets and plate for 2 RJ45 connectors aluminium Simon 400

REF. 42403020-133



BASIC INFORMATION

DESCRIPTION

For those who are looking for a electrical connection efficient and without the need to search for connections in the wall, Simon presents this kit of desk top. Product of great quality made of metal with an aluminium finish, the trim cover is made of painted steel while the profile is aluminium anodized, the covers and fastenings are designed to offer the maximum security as they are manufactured in self-extinguishing thermoplastic which prevents the expansion of the flame in case of fire. This piece belongs to the series Simon 400 and has 3 socket-outlets plug and plate for 2 RJ45 connectors, with dimensions of 2015 x 120 x 80 millimetres we find the version of 4 elements, suitable for incorrect voltages of 250 volts and current of 16 amps. A product that has a manual elevation system, thanks to which we will be able to access to it in a comfortable and simple way.

FINISH

Aluminium

MATERIAL

Metal

COMPATIBILITY

Can be combined with the range of Electric Cabling from Simon.

PACKAGING CONTENTS

Pre-wired profile, table-top supports, rear trim cover and installation manual.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

IP RATING

IP30

RAL

9006

DIELECTRIC STRENGTH

No holes or contours, with 2000V at 50 Hz for 1 minute

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

NUMBER OF RJ45 WINDOWS

2

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60°C

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 at +60°C

SNAP-FIT RJ45 PLATES

Keystone I, II and Systimax

FORMAT

Schuko

SNAP-FIT TYPE

Keystone I, II and Systimax

HEAT RESISTANCE (°C)

+70°C (according to standard IEC 60670)

NOMINAL VOLTAGE (V~)

250 V~

NUMBER OF SOCKETS

3 sockets for standard current circuit

INSULATION RESISTANCE (V-MΩ)

>5 MΩ at 500 V

TYPE OF POWER SUPPLY CONNECTOR

Wieland GST 18i male 3-pole overhead connector with 22 cm patch cord

VERSION

4 elements

CURRENT (A)

16 A

INSTALLATION AND MAINTENANCE

CLAW RANGE OF OPERATION (MM)

Between 16 and 40 mm

TYPE OF FASTENING

By tightening existing clamps in the fastening bracket.

SECURING POSSIBILITIES

Using clips included in the fastening brackets

EXTINGUISHING (°C)

+70 °C (according to standard IEC 60670)

INSTALLATION TYPE

Suitable for fixing to furniture.

MOUNTING WITHOUT ACCESSORIES

Supplied with all necessary materials for installation.

REGULATIONS

REGULATIONS

Directiva 2014/35/UE LVD;Directiva 2011/65/UE RoHS;EN 50173-1:2011;EN 50581:2012;EN 60670-1:2005;EN 60670-1:2005 A1:2013;IEC 60884-1 Ed 3.2;

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053195697

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

0.8

PRODUCT NET WEIGHT

0.8

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053195697

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

90

PACKAGING WIDTH

116

PACKAGING LENGTH

298

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

3111120

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

0.8

PACKAGING WEIGHT UNIT

KGM