Two-pole socket outlet 10A 250V~ for half element with safety device and screw terminal connection ivory Simon 27 Play

REF. **27431-61**



BASIC INFORMATION

DESCRIPTION

The security has been a maxim of Simon to the throughout his 100 years of history creating elements for electrical and electronic systems. In the sockets category, we have the Socket-outlet two-pole 16 A 250V~ of half an element and screw-terminal connection in ivory finish of the Simon 27 Play series, it includes a safety device that makes it perfect for rooms with minors in which we want to avoid any type of unexpected accident or in buildings with children such as educational centres or hospitals. It is ideal to assemble in new work or to replace in reforms carried out in certain rooms of a home or a company, being apt for replacement or export. The metal components with halogen-free thermoplastic insulation and thermoplastic trim with which it has been manufactured stand out for their durability and resistance.

FINISH

Ivory

COMPATIBILITY

Simon 27 Play, Simon 27 Neos, Simon 27 Scudo, Simon 27, Simon 27 Centralisations and Simon 44 Aqua frames

PACKAGING CONTENTS

Socket outlet with cover

ETIM CLASS

EC000125

REMARKS

Suitable for replacement or export.

TECHNICAL INFORMATION

CABLE SECTION ADMITTED (MM)

2,5 mm

NUMBER OF POSSIBLE ELEMENTS

Half element

FORMAT

Two-pole

INDICATOR FUNCTION

No

CURRENT (A)

10 A

IP RATING

IP20

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TYPE OF MECHANISM

Insertion

MONOBLOCK

No

NOMINAL VOLTAGE (V~)

250 V~

OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

STORAGE TEMPERATURE RANGE (°C)

-25 - 50 °C

VERSION

Single

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)
15

CLAW
Simon 27

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX
Universal, American, Small spaces and Centralisations

INSTALLATION DIRECTION
Horizontal, Vertical

INSTALLATION TYPE
Suitable for surface and flush mounting

TYPE OF TERMINAL CONNECTION - FUNCTION 1
Screw

REGULATIONS

REGULATIONS
Dir. 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | UNE 20315-1-1:2017 | IEC 60884-1 Ed 3.2 | UNE 20315-1-2:2017

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053252048

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING MEASUREMENT UNIT
MMT

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
0.033

PRODUCT NET WEIGHT
0.033

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053038079

UNITS CONTAINED PACKAGING
20

PACKAGING HEIGHT
52

PACKAGING WIDTH
105

PACKAGING LENGTH
220

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
1201200

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.665

PACKAGING NET WEIGHT
0.66

PACKAGING WEIGHT UNIT
KGM