

Angled voice and data plate with dust cover for 1 element with 2 RJ45 category 6A FTP aluminium Simon 500 Cima

REF. 50001086-033



BASIC INFORMATION

DESCRIPTION

Simon, we present this plate for voice and data connections of an element, has 1 and 2 RJ45 connectors, it is a plate and finished in aluminium. Supports a cabling of 22-24 AWG and has dust shutter and, in addition, it is manufactured with metal components with halogen-free thermoplastic insulation of the highest quality. This plate is part of the Simon 500 Cima series, which is characterized by being one of the faster on the market in terms of assembly. Thanks to its click-terminals, as it is not necessary to strip or braid any wire. Only insert, tighten and the piece itself to make the remainder. The collection Simon 500 Cima is the most complete solutions for wall, floor or open-plan areas, guaranteed always a high speed data transmission. Simon 500 Cima is synonymous with flexibility, functionality and security. This plate includes: Snap-fit in the plate for fastening in enclosures and an adapter and RJ45 connectors.

FINISH

Aluminium

PACKAGING CONTENTS

Angled voice and data plate with
dust cover, 2 RJ45 category 6A
FTP and installation manual

ETIM CLASS

EC000018

COMPATIBILITY

Simon 500 Cima enclosures

REMARKS

The plate is snap-fitted for mounting in vertical and horizontal enclosures without the need for an adaptor.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

DUST PROTECTION

Yes

PLATE TYPE

Angled

CABLE SECTION ADMITTED (MM)

22-24 AWG wiring

FORMAT

RJ45

RJ45 ADAPTOR MODULE

Included in voice and data plate

RJ45 CONNECTION

Without insertion tool

IP RATING

IP20

SNAP-FIT RJ45 PLATES

Keystone I, II, ATT®/Avaya®

CONNECTOR CHARACTERISTICS

category 6A FTP

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

SNAP-FIT TYPE

Keystone I, II, ATT®/Avaya®

NUMBER OF CONNECTORS

2

VERSION

Single

RJ45 CONNECTORS

Included in voice and data plate

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60 °C

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60 °C

NUMBER OF MODULES

1

INSTALLATION AND MAINTENANCE

REMOVAL OF CONNECTOR

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Specific Simon 500 Cima

INSTALLATION DIRECTION

Vertical, corresponding with the direction of the mechanisms

INSTALLATION TYPE

Fixing by direct snap-fit, no tools needed.

REMOVAL OF THE PLATE

Only with tool

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8421053097601

PACKAGING VOLUME

0.052

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

20

PACKAGING VOLUME UNIT

HLT

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

80

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING GROSS
WEIGHT

0.079

PACKAGING WIDTH

224

PACKAGING NET WEIGHT

1.58

PRODUCT NET WEIGHT

0.079

PACKAGING LENGTH

290

PACKAGING WEIGHT UNIT

KGM

