

Industrial bell 819 120-200W CCT 120°

REF. 81942038-787



BASIC INFORMATION

DESCRIPTION

Luminaire designed for industrial applications, suitable for high installations. High versatility thanks to its power and color temperature selector, which allows adapting the luminaire to each project with a single reference. Installation type: Suspended. Optics: 120°. Color temperature: 3000 / 4000 / 5000K. Power: 120 - 200W. Lumens: 36000lm. Efficiency: 180lm/w. Protection rating IP: IP65. Power supply: 100-240 V. 50/60 Hz. Dimensions: 360 mm x 148 mm.

APPLICATION

General lighting for high ceilings, Industrial lighting

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

IK CLASSIFICATION

09

IP RATING

IP65

OPERATING TEMPERATURE RANGE (°C)

-30...+45

POWER SUPPLY (V~)

100/240 V~

CONTROL

1-10 V

LIGHTING EFFICIENCY (LM/W)

180 lm/W

LUMENS (LM)

36000 lm

POWER (W)

120 - 200 W

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE

Suspension

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053440223

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8421053440223

PACKAGING VOLUME

23783625

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

145

PACKAGING GROSS WEIGHT

3.3

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

405

PACKAGING NET WEIGHT

2.4

UNITARY PACKAGING GROSS
WEIGHT

3.3

PACKAGING LENGTH

405

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

2.4