Customisable set with 4 schuko socket outlets and 1 empty element white S400 Top

REF. **42504000-130**



BASIC INFORMATION

DESCRIPTION

We are looking at a desk top customizable kit with 4 socket-outlets socket and 1 element empty, this piece is white in colour and belongs to the new Simon series 400. It has dimensions of 250 x 120 x 80 millimetres and is made for 250 volts and 16 A of intensity. Its 5 elements can be manipulated in a very simple thanks to its manual elevation system, a piece created to be perfectly in any space. The high quality materials are a fundamental characteristic of all Simon products. This kit has a trim cover painted steel, a profile of anodised aluminium and covers manufactured in self-extinguishing halogen-free thermoplastic that prevent the creation of fumes toxic and the no-propagation of the flame in case of fire management. To complete the installation of this part, we must use the functions of Simon 400 Top.

FINISH

White

MATERIAL

Metal

COMPATIBILITY

Functions of the Simon 400 range, combinable with the Simon Electric Cabling range.

PACKAGING CONTENTS

Pre-wired profile, table-top supports, rear trim cover and installation manual.

ETIM CLASS

EC002759

REMARKS

To complete the product installation combine it with the Simon 400 functions (refs. 400XXXXX-03X).

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

DIELECTRIC STRENGTH
No holes or contours, with 2000V at 50 Hz for 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)
+60°C

NUMBER OF POSSIBLE ELEMENTS
1

FORMAT
Schuko

HEAT RESISTANCE (°C)
+70°C (according to standard IEC 60670)

INSULATION RESISTANCE (V-MΩ)
>5 M? at 500 V

CURRENT (A)
16 A

IP RATING
IP30

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)
-5 at +60° C

NOMINAL VOLTAGE (V~)
250 V~

TYPE OF POWER SUPPLY CONNECTOR
Wieland® GST 18i male 3-pole overhead connector with 22 cm patch cord

RAL
9016

NUMBER OF REAR ENTRANCES
1

NUMBER OF SOCKETS
4 sockets for standard current circuit

VERSION
5 elements

INSTALLATION AND MAINTENANCE

CLAW RANGE OF OPERATION (MM)
Between 16 and 40 mm

REMOVAL OF COMPONENTS

EXTINGUISHING (°C)
+70 °C (according to standard IEC 60670)

TYPE OF FASTENING
By lateral tightening of claws provided with the enclosure. Optional possibility to fasten the enclosure with screws through the provided holes in the sides of the enclosure chassis.

INSTALLATION TYPE
Suitable for fixing to furniture.

REMOVAL OF THE PLATE
Only with tool

SECURING POSSIBILITIES
Using clips included in the fastening brackets

MOUNTING WITHOUT ACCESSORIES
Supplied with all necessary materials for installation.

REGULATIONS

REGULATIONS

Directiva 2014/35/UE LVD;Directiva 2011/65/UE RoHS;EN 50581:2012;EN 60670-1:2005;EN 60670-1:2005 A1:2013;IEC 60884-1 Ed 3.2;

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053195864

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
1.05

PRODUCT NET WEIGHT
1.05

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053195864

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
285

PACKAGING WIDTH
125

PACKAGING LENGTH
95

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
3384375

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0

PACKAGING NET WEIGHT
1.05

PACKAGING WEIGHT UNIT
KGM