

Metal flush-mount wall box kit for 3 double elements with 1 double socket, 1 dual UPS and 2 plates RJ45 graphite

Simon 500 Cima

REF. 51002302-036



BASIC INFORMATION

FINISH

Stainless steel

MATERIAL

Stainless steel

PACKAGING CONTENTS

Flush-mount wall kit, metal
partition wall, ground
connection cable and installation
manual

ETIM CLASS

EC002601

REMARKS

The frame holders include linkable parts that form blocks, allowing the electrical part to be separated from the voice and data part for ease of maintenance

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

CABLE SECTION ADMITTED (MM)

From 1,5 to 2,5 mm

NUMBER OF CONNECTIONS PER TERMINAL

1 terminal connection for click terminal connection system and 2 terminal connections for screw terminal connection system

COMPATIBLE WITH CONNECTORS

Simon®, AMP netconnect® Standard 110, SL110, SL Tool-less, 216000 and 216005, Brand-Rex®, ADC Krone® KM8 Keystone, BeldenCDT® Giga Flex Keystone, Ersys®, General Cable®, Molex®, Panduit® Netkey, Ortronics® Clarity TechChoice Keystone, Rit® and other manufacturers with Keystone snap-fit system.

NUMBER OF CONNECTORS

2

RJ45 CONNECTORS

Not included

DUST SHUTTER

Yes

ELECTROMAGNETIC IMMUNITY FOR VDM WIRING

Secured by installing the metal partition wall in the rail fitted into the box for this purpose.

FORMAT

Schuko

NUMBER OF ENCLOSURES FOR GROUND CONNECTION

Dedicated rail in the box structure

INDICATOR FUNCTION

Yes

CURRENT (A)

16 A

IP RATING

IP20

LED CONSUMPTION INDICATOR (mA)

0.55

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TYPE OF MECHANISM

Insertion

NUMBER OF MODULES

6

MONOBLOCK

Yes

NUMBER OF PLATES

2 voice and data plates

PLATE TYPE

Flat

RECESS DIMENSION (MM)

170 x 208 mm

RJ45 ADAPTOR MODULE

Included in voice and data plates

NUMBER OF SIDE ENTRANCES

4

SNAP-FIT RJ45 PLATES

Keystone I, II, ATT®/Avaya®

SNAP-FIT TYPE

Keystone I, Keystone II and Systemax

NUMBER OF SOCKETS

1 double socket for standard current circuit and 1 double socket for stable current circuit

VERSION

3 double elements

VOLTAGE (V~)

250 V~

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

0

CLAW RANGE OF OPERATION (MM)

Between 2 and 30 mm

REMOVAL OF CONNECTOR

REMOVAL OF COVER

Only with tool

TYPE OF FASTENING

Using the claws included in the enclosure, in combination with aggregates, binders, additives, etc.

REMOVAL OF THE FRAME

Only with tool

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Specific Simon 500 Cima
(supplied with the frame)

INSTALLATION DIRECTION

Vertical, corresponding with the
direction of the mechanisms

INSTALLATION TYPE

Suitable for flush mounting on
the wall

REMOVAL OF THE PLATE

Only with tool

REMOVAL OF THE SOCKET

Only with tool

TYPE OF TERMINAL CONNECTION - FUNCTION 1

1 click connection (1 click®)

NUMBER OF TERMINALS

3 inputs and 3 outputs

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + Directive 2011/65/UE RoHS + EN 50581:2012 + EN 60670-1:2005 + IEC 60884-1
Ed 3.2

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053100820

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

1.718

PRODUCT NET WEIGHT

1.718

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053100820

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

69

PACKAGING WIDTH

189

PACKAGING LENGTH

226

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

2.947

PACKAGING VOLUME UNIT

DMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

1.718

PACKAGING WEIGHT UNIT

KGM

