

Modular luminaire 720 Advance M4 120X30 WW CLC DALI

REF. 72061540-883



BASIC INFORMATION

DESCRIPTION

Control and regulate the natural light of the space and armonícelo with its light artificial, with the luminaire 720 modular Advance M4 of the collection Simon indoor lighting. Thanks to its system of constant light control (CLC) will take the maximum the natural light in concordancia with light artificial. It also has interface of adjustment DALI to maximize the functionalities of its luminaire. With translucent optics, this luminaire provides a warm lighting with luminous light flux 3200 lm for WW y a consumption of 28 W. This comprising multiple LEDs to ensure a longer energy savings, with a service life of 1000.000 hours for the L70 at 25 ° C and 40,000 hours for the L90. It is also compatible with a voltage of 230 Volts AC power and 50-60 Hz. Finished in white and designed for installation both flush mounted and surface-mounted in false ceiling and hardware, this luminaire integrates seamlessly into all types of spaces, adding a current and minimalist style.

DIFFUSER MATERIAL

PMMA

PACKAGING CONTENTS

1 unit

APPLICATION

General lighting

ETIM CLASS

EC002892

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

DRIVER INCLUDED

Yes

LIGHTING EFFICIENCY (LM/W)

114 lm/W

IP RATING

IP44

ELECTRICAL CLASS

Type 2

LUMENS (LM)

3200 lm

OPERATING TEMPERATURE RANGE (°C)

40 °C maximum

INTEGRATED POWER SUPPLY

Yes

LUMENS/W

3200 lm/28W

POWER SUPPLY (V~)

230 V~

L70 (°C)

100,000 h at 25 °C

OPTICS

Translucent

COLOR TEMPERATURE (K)

3000 K

L90 (°C)

40,000 h at 25 °C

PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

CONTROL

CLC,DALI

LIGHT BEAM APERTURE ANGLE (°)

120°

POWER (W)

28 W

CRI

82

COLOR TYPE

WW

SERVICE LIFE

50.000 h

CHROMATICS CRI ICONS

CRI
82

INSTALLATION AND MAINTENANCE

INSTALLATION ALTERNATIVES

Plaster ceiling, surface mount, concealed or semi-concealed profile.

MINIMUM INSTALLATION HEIGHT

120

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Quick connector

INSTALLATION TYPE

False ceiling, visible hardware

REGULATIONS

WARRANTY

5 years 50,000 h

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

6.5

PRODUCT NET WEIGHT

6

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053192207

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

65

PACKAGING WIDTH

300

PACKAGING LENGTH

1200

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

23400000

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

6

PACKAGING WEIGHT UNIT

KGM