

## Complete set with 6 schuko socket outlets black S400 Top

REF. 42606000-138



### BASIC INFORMATION

#### DESCRIPTION

Desk top complete kit with 6 socket-outlet Schuko, black in colour and of the Simon series 400. Its dimensions are 295 x 120 x 80 mm and its type manual elevation and has a current of 16 A and works with a voltage of 250V. It can withstand heat of over 70 and its trim cover is made of painted steel, profile in anodised aluminium, covers and fastenings in self-extinguishing thermoplastic and halogen-free, which guarantees the no-propagation of the flame in case of fire and low toxicity in case of smoke. It is a kit suitable to be flush mounted in furniture and is fixed through clamps that are pages and to clean this kit only have to clean with a soft, dry cloth and do not use cloths or abrasive cleaners containing chlorine in its formulation, as it could be damaged and does not operate correctly.

#### FINISH

Black

#### MATERIAL

Metal

#### COMPATIBILITY

Can be combined with the range of Electric Cabling from Simon.

#### PACKAGING CONTENTS

Pre-wired profile, table-top supports, rear trim cover and installation manual.

#### ETIM CLASS

EC002759

## TECHNICAL INFORMATION

### AVAILABLE MARKET

CE

### INSULATION RESISTANCE (V-MΩ)

>5 MΩ at 500 V

### NOMINAL VOLTAGE (V~)

250 V~

### DIELECTRIC STRENGTH

No holes or contours, with 2000V at 50 Hz for 1 minute

### CURRENT (A)

16 A

### TYPE OF POWER SUPPLY CONNECTOR

Wieland  GST 18i male 3-pole overhead connector with 22 cm patch cord

### MAX TEMP DURING CONSTRUCTION WORK (°C)

+60  C

### IP RATING

IP30

### RAL

9005

### FORMAT

Schuko

### MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

### NUMBER OF SOCKETS

6 sockets for standard current circuit

### HEAT RESISTANCE (°C)

+70°C (according to standard IEC 60670)

### TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 at +60  C

### VERSION

6 elements

## INSTALLATION AND MAINTENANCE

### CLAW RANGE OF OPERATION (MM)

Between 16 and 40 mm

### TYPE OF FASTENING

By tightening existing clamps in the fastening bracket.

### SECURING POSSIBILITIES

Using clips included in the fastening brackets

### EXTINGUISHING (°C)

+70 °C (according to standard IEC 60670)

### INSTALLATION TYPE

Suitable for fixing to furniture.

### MOUNTING WITHOUT ACCESSORIES

Supplied with all necessary materials for installation.

## REGULATIONS

### REGULATIONS

Directiva 2014/35/UE LVD;Directiva 2011/65/UE RoHS;EN 50581:2012;EN 60670-1:2005;EN 60670-1:2005 A1:2013;IEC 60884-1 Ed 3.2;

## LOGISTICS INFORMATION

### UNITARY EAN CODE

8421053196205

### UNITARY PACKAGING HEIGHT

0

### UNITARY PACKAGING WIDTH

0

### UNITARY PACKAGING LENGTH

0

### UNITARY PACKAGING VOLUME

0

### UNITARY PACKAGING GROSS WEIGHT

1.15

### PRODUCT NET WEIGHT

1.15

### UNITARY PACKAGING WEIGHT UNIT

KGM

### PACKAGING EAN

8421053196205

### UNITS CONTAINED PACKAGING

1

### PACKAGING HEIGHT

330

### PACKAGING WIDTH

125

### PACKAGING LENGTH

95

### PACKAGING MEASUREMENT UNIT

MMT

### PACKAGING VOLUME

3918750

### PACKAGING VOLUME UNIT

MMQ

### PACKAGING GROSS WEIGHT

0

### PACKAGING NET WEIGHT

1.15

### PACKAGING WEIGHT UNIT

KGM