

Square shallow floor box for 4 elements in concrete or raised floor grey Simon 500 Cima

REF. 52050202-035



BASIC INFORMATION

DESCRIPTION

The square floor box of the range of Simon 500 in grey colour, it is specially designed for installation in garden a low depth. It is valid for both concrete floors and for raised garden, that is slightly high on the concrete socket. With dimensions of 252 x 180 millimetres and 69 millimetres of depth, the square floor box Simon 500 can be supplied electrical power to a total of 4 elements. If you choose to install by recessing in concrete floor, you have to complete the installation with a plastic tray (ref.G201). It is also possible to accompany a trim cover (Ref. 52053202-035), if it is not installed in the same lining. This box has the added value of being composed of high quality materials based on the thermoplastic self-extruding, you also reduce the flame spread in case of fire a possible due to the room where it is. This same, has the capacity to reduce the toxicity of smoke.

FINISH

Grey

MATERIAL

Plastic

COMPATIBILITY

Simon 500 Cima and Simon 27
Play/Simon K45 mechanisms
(using a specific adaptor)

PACKAGING CONTENTS

Floor box and installation
manual

ETIM CLASS

EC000024

REMARKS

To complete the installation of the product in concrete floors, once configured, it must be combined with a plastic tray (ref.G201). Alternatively, it may be combined with flush-mount trim cover (ref.52053202-035) in cases where the same floor lining is not installed.

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

PROTECTION AGAINST DIRECT
ACCESS OF CONTACTS

PROTECTION AGAINST ENTRY OF
DUST AND SMALL OBJECTS

AVAILABLE IN

NUMBER OF CLAMP-HOLDER
HOLES

DIELECTRIC STRENGTH

MAX TEMP DURING
CONSTRUCTION WORK (°C)

HEAT RESISTANCE (°C)

IK CLASSIFICATION

INSULATION RESISTANCE (V-MΩ)

IP RATING

KIT AVAILABILITY

MAINTENANCE

TEMPERATURE RANGE DURING
INSTALLATION (°C)

NUMBER OF MODULES

NUMBER OF PRE-PUNCHED
HOLES 55 X 20 MM

RAL

RECESS DIMENSION (MM)

NUMBER OF SIDE ENTRANCES

VERSION

INSTALLATION AND MAINTENANCE

CLAW RANGE OF OPERATION
(MM)

REMOVAL OF COMPONENTS

NUMBER OF COVER OPENING
POSITIONS

EXTINGUISHING (°C)

TYPE OF FASTENING

CAN BE INSTALLED IN TRAY

INSTALLATION DIRECTION

INSTALLATION TYPE

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + EN 60670-23:2008

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053093184

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

1.25

PRODUCT NET WEIGHT

1.25

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053093184

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

80

PACKAGING WIDTH

210

PACKAGING LENGTH

280

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

4704000

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

1.25

PACKAGING WEIGHT UNIT

KGM

