

Luminaire A30 BT Mesh 20,7W 4000K with detector 8m HF+LUX white IP54 IK10

REF. 89391600-204



BASIC INFORMATION

DESCRIPTION

Luminaire with integrated HF detector and bluetooth connectivity. The power is 20.7 W, the luminous flux is 2534 lm, and the color temperature is 4000 K.

The maximum installation height is 4m and the installation is surface-mounted. The detection range is 8m, and the detection angle is 360°.

The brightness regulation range is 2 - 2000 lux, and the timing range is 10 s - 60 min.

The luminaire is configured via a bluetooth application. Possibility of interconnection between luminaires through bluetooth mesh.

The power supply voltage is 220 - 240 VAC. The operating temperature is: -20 - 40 °C.

Protection class IP 54 and IK 10 and dimensions: Ø 330 x 69 mm.

5-year warranty.

For more product information, visit the STEINEL website by clicking [here](#).

FINISH

White

ETIM CLASS

EC002892

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

IP RATING

IP54

POWER SUPPLY (V~)

220/240 V~

IK CLASSIFICATION

10

OPERATING TEMPERATURE RANGE (°C)

-20...+40

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE

Surface mounting

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053429839

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

2.551

PRODUCT NET WEIGHT

1.889

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053429839

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

380

PACKAGING WIDTH

380

PACKAGING LENGTH

85

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

2325323

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

2.551

PACKAGING NET WEIGHT

1.889

PACKAGING WEIGHT UNIT

KGM