

## Customisable set with 4 schuko socket outlets and 1 empty element black S400 Top

REF. 42504000-138



## BASIC INFORMATION

### DESCRIPTION

Thanks to this kit of desk top customizable in black colour belonging to the series Simon 400 Top, and has 4 socket outlets and one empty element, we can integrate over the furniture all the necessary connections to avoid the need of lengthy wires on the floor or search connections in distant walls. With dimensions of 250 x 120 x 80 millimetres integrates perfectly its 5 elements. Manufactured for 250 volts and 16 amps. It has a connector figure Wieland ® gst18i 3 poles male in-line with patch cord of 22 cm and has a dielectric strength with no holes or contours with 2000 volts to 50 Hertz rate for 1 minute. A piece made with materials that provide a cutting-edge design as the trim cover painted steel, and a great resistance thanks to its profile in anodised aluminium.

### FINISH

Black

### MATERIAL

Metal

### COMPATIBILITY

Functions of the Simon 400 range, combinable with the Simon Electric Cabling range.

### PACKAGING CONTENTS

Pre-wired profile, table-top supports, rear trim cover and installation manual.

### ETIM CLASS

EC002759

### REMARKS

To complete the product installation combine it with the Simon 400 functions (refs. 400XXXXX-03X).

## TECHNICAL INFORMATION

### AVAILABLE MARKET

CE

### DIELECTRIC STRENGTH

No holes or contours, with 2000V at 50 Hz for 1 minute

### MAX TEMP DURING CONSTRUCTION WORK (°C)

+60  C

### NUMBER OF POSSIBLE ELEMENTS

1

### FORMAT

Schuko

### HEAT RESISTANCE (°C)

+70°C (according to standard IEC 60670)

### INSULATION RESISTANCE (V-MΩ)

>5 MΩ at 500 V

### CURRENT (A)

16 A

### IP RATING

IP30

### MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

### TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 at +60  C

### TYPE OF POWER SUPPLY CONNECTOR

Wieland  GST 18i male 3-pole overhead connector with 22 cm patch cord

### RAL

9005

### NUMBER OF REAR ENTRANCES

1

### NUMBER OF SOCKETS

4 sockets for standard current circuit

### VERSION

5 elements

### VOLTAGE (V~)

250 V~

## INSTALLATION AND MAINTENANCE

### CLAW RANGE OF OPERATION (MM)

Between 16 and 40 mm

### REMOVAL OF COMPONENTS

### EXTINGUISHING (°C)

+70 °C (according to standard IEC 60670)

### TYPE OF FASTENING

By lateral tightening of claws provided with the enclosure. Optional possibility to fasten the enclosure with screws through the provided holes in the sides of the enclosure chassis.

### INSTALLATION TYPE

Suitable for fixing to furniture.

### REMOVAL OF THE PLATE

Only with tool

### SECURING POSSIBILITIES

Using clips included in the fastening brackets

### MOUNTING WITHOUT ACCESSORIES

Supplied with all necessary materials for installation.

## REGULATIONS

### REGULATIONS

Directiva 2014/35/UE LVD;Directiva 2011/65/UE RoHS;EN 50581:2012;EN 60670-1:2005;EN 60670-1:2005 A1:2013;IEC 60884-1 Ed 3.2;

## LOGISTICS INFORMATION

### UNITARY EAN CODE

8421053195888

### UNITARY PACKAGING HEIGHT

0

### UNITARY PACKAGING WIDTH

0

### UNITARY PACKAGING LENGTH

0

### UNITARY PACKAGING VOLUME

0

### UNITARY PACKAGING GROSS WEIGHT

1.05

### PRODUCT NET WEIGHT

1.05

### UNITARY PACKAGING WEIGHT UNIT

KGM

### PACKAGING EAN

8421053195888

### UNITS CONTAINED PACKAGING

1

### PACKAGING HEIGHT

285

### PACKAGING WIDTH

125

### PACKAGING LENGTH

95

### PACKAGING MEASUREMENT UNIT

MMT

### PACKAGING VOLUME

3384375

### PACKAGING VOLUME UNIT

MMQ

### PACKAGING GROSS WEIGHT

0

### PACKAGING NET WEIGHT

1.05

### PACKAGING WEIGHT UNIT

KGM