

Pull-cord push button 10A 250V~ with fast terminal connection system white Simon 31

REF. 31652-30



BASIC INFORMATION

DESCRIPTION

Pull cord push button with quick terminal connection and finished in white of the Simon 31 series. This type of Simon 31 push button is available in 2 different finishes, it is recommended to use a frame the same colour as the selected rocker. The current is 10A and a voltage of 250V, and it supports a cable section from 0.2 to 0.5 mm, with a wire stripping of 13 mm, approximately. It can be installed in places with a temperature of between 5 and 40°C, although it is capable of withstanding extreme temperatures of -25 to 50°C, approximately. It is made of metal components with halogen-free insulation and the trim is made of thermoset material. These materials are very easy to clean, as you just need a soft cloth slightly dampened in soapy water to make it in perfect condition. It also measuring 64x65mm.

FINISH

White

PACKAGING CONTENTS

Mechanism with rocker

COMPATIBILITY

Simon 31 frames

ETIM CLASS

EC000029

REMARKS

Available in 2 finishes. It is recommended to choose a frame the same colour as the selected rocker.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

CURRENT (A)

10 AX

OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

CABLE SECTION ADMITTED (MM)

From 0,2 to 0,5 mm

IP RATING

IP20

STORAGE TEMPERATURE RANGE (°C)

-25 - 50 °C

NUMBER OF POSSIBLE ELEMENTS

1 element

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

VERSION

Single

INDICATOR FUNCTION

No

TYPE OF MECHANISM

Pull handler

VOLTAGE (V~)

250 V~

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

13

INSTALLATION TYPE

Suitable for surface and flush mounting

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Screw

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + Directive 2011/65/UE RoHS + EN 61058:2002 + EN 61058:2002 A2:2008 + EN 61058-2-1:2011

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
3409560

UNITARY PACKAGING VOLUME
UNIT
MMQ

UNITARY PACKAGING GROSS
WEIGHT
0.102

PRODUCT NET WEIGHT
0.102

UNITARY PACKAGING WEIGHT
UNIT
KGM

PACKAGING EAN
8421053006436

UNITS CONTAINED PACKAGING
10

PACKAGING HEIGHT
82

PACKAGING WIDTH
165

PACKAGING LENGTH
252

PACKAGING MEASUREMENT
UNIT
MMT

PACKAGING VOLUME
3409560

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
1.02

PACKAGING NET WEIGHT
1.02

PACKAGING WEIGHT UNIT
KGM