

Flat voice and data plate with dust cover for 1 element with 1 RJ45 category 6 FTP white Simon 500 Cima

REF. 50003185-030



BASIC INFORMATION

DESCRIPTION

The Simon 500 Cima series lands with the aim of improve the workplace solutions in the different spaces. One sample of this is this plate of voice and data flat plate with 1 element for 1 RJ45 category 6 FTP. The mechanism is finished in white and does not include dust shutter. In several to their physical features, the piece measures 50x50x45,4 mm and is in compliance with the regulations, it also has clips designed for optimum fastening in vertical and horizontal enclosures without that is essential adapter. The plate is made of metal elements with halogen-free thermoplastic of character self-extinguishing and halogen-free. This material that provides maximum security in case of fire, as this helps to prevent the propagation of the fire. It is very important to give you a proper maintenance to the article to prolong its service life., use a soft, dry cloth.

FINISH

White

PACKAGING CONTENTS

Flat voice and data plate without dust cover, RJ45 category 6 FTP connector and installation manual

ETIM CLASS

EC000018

COMPATIBILITY

Simon 500 Cima enclosures

REMARKS

The plate is snap-fitted for mounting in vertical and horizontal enclosures without the need for an adaptor.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

DUST PROTECTION

No

PLATE TYPE

Flat

CABLE SECTION ADMITTED (MM)

22-26 AWG wiring

FORMAT

RJ45

RAL

9003

RJ45 CONNECTION

Without insertion tool

IP RATING

IP20

RJ45 ADAPTOR MODULE

Included in voice and data plate

CONNECTOR CHARACTERISTICS

category 6 FTP

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

SNAP-FIT RJ45 PLATES

Keystone I, II, ATT®/Avaya®

NUMBER OF CONNECTORS

1

SNAP-FIT TYPE

Keystone I, II, ATT®/Avaya®

RJ45 CONNECTORS

Included in voice and data plate

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60 °C

VERSION

Single

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60 °C

NUMBER OF MODULES

1

INSTALLATION AND MAINTENANCE

REMOVAL OF CONNECTOR

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Specific Simon 500 Cima

INSTALLATION DIRECTION

Vertical, corresponding with the direction of the mechanisms

INSTALLATION TYPE

Fixing by direct snap-fit, no tools needed.

REMOVAL OF THE PLATE

Only with tool

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
220

UNITARY PACKAGING WIDTH
400

UNITARY PACKAGING LENGTH
430

UNITARY PACKAGING
MEASUREMENT UNIT
MMT

UNITARY PACKAGING VOLUME
37840000

UNITARY PACKAGING VOLUME
UNIT
MMQ

UNITARY PACKAGING GROSS
WEIGHT
0.069

PRODUCT NET WEIGHT
0.069

UNITARY PACKAGING WEIGHT
UNIT
KGM

PACKAGING EAN
8421053098134

UNITS CONTAINED PACKAGING
20

PACKAGING HEIGHT
82

PACKAGING WIDTH
165

PACKAGING LENGTH
223

PACKAGING MEASUREMENT
UNIT
MMT

PACKAGING VOLUME
0.052

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0

PACKAGING NET WEIGHT
1.38

PACKAGING WEIGHT UNIT
KGM

