

## LOOP wall-mounted luminaire On/Off 3000 K Black

REF. 91220054-388



### BASIC INFORMATION

#### BODY MATERIAL

Die-cast aluminium

#### PACKAGING CONTENTS

1 Unit

#### ETIM CLASS

EC002892

#### APPLICATION

Domestic, Office, Retail, Hotel, Contract

#### PACKAGING DIMENSIONS (MM)

16x224x171 mm

## TECHNICAL INFORMATION

### FREQUENCY

50 - 60 Hz

### CRI

80

### COLOR TYPE

NW

### IP RATING

IP20

### DIRECTIONAL

Yes

### LIGHTING EFFICIENCY (LM/W)

hasta 18 lm/W

### OPERATING TEMPERATURE RANGE (°C)

0 - 35 °C

### DRIVER INCLUDED

Yes

### LUMENS (LM)

77 lm

### POWER SUPPLY (V~)

110/240 V~

### ELECTRICAL CLASS

II

### NUMBER OF LUMINAIRES

1

### RAL

9005

### ENERGY EFFICIENCY

A+

### MACADAM STEPS

<3 Step MacAdam

### COLOR TEMPERATURE (K)

3000 K

### L70 (°C)

20000h at 25°C

### OPTICS

General 112°

### CONTROL

On/Off

### LIGHT BEAM APERTURE ANGLE (°)

112°

### POWER FACTOR (Φ)

> 0,9

### POWER (W)

4.5 W

## INSTALLATION AND MAINTENANCE

### INSTALLATION TYPE

Trimless

## REGULATIONS

### EAC MARKED

Yes

### ECORRAE MARKED

No

### WARRANTY

3 years

## LOGISTICS INFORMATION

### UNITARY PACKAGING HEIGHT

0

### UNITARY PACKAGING WEIGHT UNIT

KGM

### PACKAGING MEASUREMENT UNIT

MMT

### UNITARY PACKAGING WIDTH

0

### PACKAGING EAN

8436547041855

### PACKAGING VOLUME

4627350

### UNITARY PACKAGING LENGTH

0

### UNITS CONTAINED PACKAGING

1

### PACKAGING VOLUME UNIT

MMQ

### UNITARY PACKAGING VOLUME

0

### PACKAGING HEIGHT

116

### PACKAGING GROSS WEIGHT

0.39

### UNITARY PACKAGING GROSS WEIGHT

0.4

### PACKAGING WIDTH

171

### PACKAGING NET WEIGHT

0.35

### PRODUCT NET WEIGHT

0.35

### PACKAGING LENGTH

224

### PACKAGING WEIGHT UNIT

KGM