

Ofiblock Compact for 5 useful mechanisms with rear diecut in the second to last and previous position

REF. KFC105NL2/14



BASIC INFORMATION

DESCRIPTION

Anodized aluminum Ofiblock Compact profile designed to provide maximum functionality in a compact size, enabling the convergence of power, voice, data, and multimedia solutions. With its minimal depth and broad range of accessories, it supports multiple installation options on raised floors, walls, furniture, metallic surfaces with magnets, or on DIN rails. Developed to suit the specific needs of each space, it allows for a custom configuration with K45 modules, offering a versatile and efficient solution. Supplied with two side covers for quick connectors (Wieland type), providing the Ofiblock Compact with electrical cable input and output. It also features two rear knockouts in the penultimate and antepenultimate positions for optimal routing of voice, data, or multimedia cabling to the K45 modules you choose to install. These will be electromagnetically protected and shielded thanks to the included protective trays. Self-extinguishing, halogen-free thermoplastic covers ensure safety in case of fire.

FINISH

Black

COMPATIBILITY

Functions of the Simon K45 range and combinable with the Simon Electrical Wiring range.

ETIM CLASS

EC002759

MATERIAL

Metal, Plastic

REMARKS

Profile with higher compactness to enable convergence of power, voice, data and multimedia solutions with minimal depth

TECHNICAL INFORMATION

HEAT RESISTANCE (°C)

+125°C (according to standard IEC 60670)

IP RATING

IP4X

KIT AVAILABILITY

No

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

MONOBLOCK

No

RAL

7021

INSTALLATION AND MAINTENANCE

REMOVAL OF COMPONENTS

Only with tool

EXTINGUISHING (°C)

+850 °C (according to standard IEC 60670)

INSTALLATION DIRECTION

Horizontal, Vertical

SECURING POSSIBILITIES

Its design allows it to be surface-mounted on the wall, on table-top furniture, under a desk, on a raised floor, a metal surface with magnet, or on a DIN rail using specific fastening accessories.

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053290569

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

0.287

PRODUCT NET WEIGHT

0.287

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053290569

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

60

PACKAGING WIDTH

55

PACKAGING LENGTH

320

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

1056000

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.325

PACKAGING NET WEIGHT

0.287

PACKAGING WEIGHT UNIT

KGM