

Satellite socket single F type female with trim plate black Simon K45

REF. K102C/14



BASIC INFORMATION

DESCRIPTION

In an original finishes in black, the simple F type female satellite socket with trim plate and insertion by welding and form part of our collection Simon K45 and is suitable both for surface and flush mounting, has dimensions of 22.5x45 mm, a thickness of 42,9 mm and is made of metal materials with thermoplastic insulation self-extinguishing halogen-free in order to ensure that is no flame spread in case of fire, along with a very low toxicity in the event of smoke generation. There are some important as data to be taken into account, we inform you that the maximum recommended length of cabling is 90 metres. If you are in which they were looking for the latest in technology for your home, you are of congratulations, as the series Simon K45 has been specially designed to satisfy the desires of the most demanding, and that is that our I wish to innovate and improve we put as one of the brand in the sector. So that you the games and confident in our specialists.

FINISH

Black

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-038)

PACKAGING CONTENTS

Simple F type female satellite socket

ETIM CLASS

EC000439

REMARKS

Maximum wire length recommended; 90 metres (RG-6 cable). For additional information, please read the product instruction sheet

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

IP RATING

IP20

STORAGE TEMPERATURE RANGE (°C)

-25 - 50 °C

CABLE SECTION ADMITTED (MM)

From 6 to 8 mm

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

VERSION

Single

CONNECTOR TYPE

SAT

NUMBER OF WIRES

1

NUMBER OF CONTACTS

1

OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

NUMBER OF POSSIBLE ELEMENTS

1/2 element

RAL

7021

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-038)

INSTALLATION TYPE

Suitable for surface and flush mounting

REGULATIONS

REGULATIONS

Dir. 2014/30/UE EMC | Dir. 2011/65/UE RoHS + post. mod. | EN 50083-2:2012 + A1:2015 | EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.014

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING VOLUME

911400

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8426436046535

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

91140

UNITS CONTAINED PACKAGING

10

PACKAGING GROSS WEIGHT

0.14

UNITARY PACKAGING VOLUME
UNIT

MMQ

PACKAGING HEIGHT

70

PACKAGING NET WEIGHT

0.14

UNITARY PACKAGING GROSS
WEIGHT

0.014

PACKAGING WIDTH

93

PACKAGING WEIGHT UNIT

KGM

PACKAGING LENGTH

140